

15-185-12361-0000

STATE OF KANSAS  
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

OR

FORMATION PLUGGING RECORD

Strike out upper line  
when reporting plug-  
ging off formations.

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
800 Bittling Building  
Wichita, Kansas

NORTH


Locate well correctly on above  
Section Plat

Stafford County. Sec. 22 Twp. 24S Rge. 13 (E) 13 (W)  
Location as "NE 1/4 NW 1/4 SW 1/4" or footage from lines 440' N & 440' W of E/4 Cor.  
Lease Owner Continental Oil Company  
Lease Name Mary Keller Well No. 2  
Office Address P. O. Box 1267, Ponca City, Oklahoma  
Character of Well (completed as Oil, Gas or Dry Hole) Dry Hole  
Date, well completed 4/28/41 19  
Application for plugging filed 4/29/41 19  
Application for plugging approved 4/29/41 19  
Plugging Commenced 4/29/41 19  
Plugging Completed 4/29/41 19  
Reason for abandonment of well or producing formation Dry hole  
If a producing well is abandoned, date of last production No production 19  
Was permission obtained from the Conservation Division or its agents before plugging was com-  
menced? Yes

Name of Conservation Agent who supervised plugging of this well Mr. C. T. Alexander, Great Bend, Kansas  
Producing formation Arbuckle Lime Depth to top 4125' Bottom 4134' Total Depth of Well 4134' Feet  
Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				10-3/4"	437' 2"	None

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

The hole was filled with heavy mud to within 437' of the top, a wood plug was set at this depth and cemented with 10 sacks of cement. The hole was then filled with heavy mud to within 14' of the top, a wood plug was set at this depth and cemented with 7 sacks of cement. The hole was then filled with heavy mud to the top and a steel cap was welded over the 10-3/4" casing.

5-24-41

pd  
5/17/41  
H.S.

PLUGGING  
FILE 22 24 23W  
BOOK PAGE 135 LINE 21

MAY 24  
WIKS BUREAU  
STATIONER

(If additional description is necessary, use BACK of this sheet)  
Correspondence regarding this well should be addressed to F. L. Dunn, c/o Continental Oil Company,  
Address R.F.D. #4, Lyons, Kansas

STATE OF Kansas, COUNTY OF Rice, ss.

(employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) F. L. Dunn

R.F.D. #4, Lyons, Kansas  
(Address)

SUBSCRIBED AND SWORN to before me this 22nd day of May 19 41

My commission expires October 21, 1944

Lewis M. C. Quire  
Notary Public.

WELL RECORD

I, the undersigned, being first duly sworn upon oath, state that this well record is true, correct and complete according to the records of this office and to the best of my knowledge and belief.

Name and title of representative of company  
Z. L. [Signature] No. 1 Public  
Subscribed and sworn to before me this the 23rd day of May, 1941  
My Commission expires October 21, 1944

PROPERTY OF Continental Oil Company  
Record of Well No. 2 M. Keller Farm  
Location  
440' North 440' West of the E/4 corner of  
Sec. 29 Twp. 34S Range. 19W County. Stafford State. Kansas  
Rig Commenced Rig Completed  
Rig Contractor  
Drilling Commenced 4/9/41 Drilling Completed 4/28/41  
Contractor. Parker Drilling Co. Price per foot \$.

CASING AND TUBING RECORD

Table with columns: SIZE, FEET, MAKE, SIZE, FEET, MAKE. Rows include Conductor 20 in., 15 1/2 in., 12 in., 10 in., 8 3/4 in., 8 1/4 in., 6 5/8 in. and 6 1/4 in., 5 3/16 in., 4 7/8 in. MAKE includes L. W.

Water Well ft. depth, Casing ft.

Table with columns: NAME OF SANDS, TOP, BOTTOM, FEET OF SAND, INITIAL TORPEDO (Quarts, Date of Shot). Row: Arbuckle Lime, 4135', 4134', 9'.

Record of Sand and Oil Showing DRY

How Tubed, Plugged, Production first 24 hours, Details of shot, County, Recorded, Sec., Twp., R.

Table with columns: DATE CLEANED OUT, TORPEDOED (Quarts, Date Re-Shot). Includes a stamp: PLUGGING FILE BOX 22 24 135 INE 31.

WELL LOG

FORMATION	FROM	TO
sand & clay surface sand	0	125
red bed & shale	125	150
red bed & sand	150	445
shale and shells	445	800
salt & shale	800	1265
shale & shells	1265	1500
lime	1500	1685
lime & shale broken	1685	1735
lime	1735	1830
sand sharp	1830	1884
lime	1884	1908
shale and shells	1908	1932
shale and lime	1932	1970
sandy lime	1970	2080
lime	2080	2105
lime & shale	2105	2135
lime	2135	2180
lime broken	2180	2305
lime	2305	2390
broken lime & shale	2390	2460
shale and lime	2460	2565
shale & shells	2565	2675
lime	2675	2825
shale & lime	2825	2900
lime	2900	2940
shale & sand	2940	2965
shale & shells	2965	3020
lime	3020	3200
sandy shale	3200	3215
lime	3215	3260
lime & shale	3260	3460
lime	3460	3470
shale & shells	3470	3495
lime	3495	3545
lime dense	3545	3585
lime	3585	3630
lime soft	3630	3662
lime	3662	3669
lime with shale streaks	3669	3800
lime & shale	3800	3850
cherty lime	3850	3880
chert	3880	3892
broken lime & shale	3892	3906
lime with shale	3906	3929
chert & shale	3929	3932
chert	3932	3979
cherty lime	3979	3984
chert	3984	3998
lime with chert streaks	3998	4017
lime with chert	4017	4037
lime with shale	4037	4062
broken lime & shale	4062	4104
shale	4104	4124
lime	4124	4127
lime	4127	4157

Elevation from derrick floor level 1927'.

Run 437'2" of 10-3/4" OD 40# 8-thd L.W. casing; set at 434'; cemented with 400 sacks of cement.

Top of Arbuckle Lime 4125'.

4/27/41 - Cored from <sup>342</sup>4126' to 4129' recovered 2 1/2' of Arbuckle Dolomite w/ few stains of oil & odor of sulphur - Cored from 4129' to 4134', recovered 5' Dolomite w/ few oil stains & odor of sulphur.

4/29/41 - Plugged and abandoned.

Total depth 4134'.

Note: All of above footages except elevation are calculated from the ground level.

.....

3 1010 15  
 4125  
 - 4927  
 - 2188

FLD-JL 5/28/41  
 LFG (3) File (1)