

1091060

TO: STATE CORPORATION COMMISSION

API NUMBER 15-185-23,101-0000
SW SE SE SEC. 10, T 24 S, R 13 W

CONSERVATION DIVISION - PLUGGING SECTION 330 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 990 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202

LEASE NAME ROOHMS A WELL # 2

TECHNICIAN'S PLUGGING REPORT

COUNTY STAFFORD 133.64

OPERATOR LICENSE # 5097

WELL TOTAL DEPTH 4112 FEET

OPERATOR: MARTIN OIL PRODUCERS, INC. PRODUCTION CSG: SIZE " FEET

NAME AND 150 N MAIN #1010 SURFACE CASING: SIZE 8 5/8" @ 237' WITH SX

ADDRESS WICHITA, KS 67202 CONDUCTOR CSG: SIZE " @ '

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL D/A X

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR DUKE DRILLING LICENSE NUMBER 5929

ADDRESS 100 S MAIN, SUITE 410 WICHITA, KS 67202-3737

COMPANY TO PLUG AT: HOUR: 4:00 PM DAY: 01 MONTH: 06 YEAR: 2000

PLUGGING PROPOSAL RECEIVED FROM JOHN

(COMPANY NAME) DUKE DRILLING (PHONE) 316-267-1331

WERE:

1ST PLUG AT 800' WITH 50 SX CEMENT. 2ND PLUG AT 270' WITH 50 SX CEMENT.

3RD PLUG AT 40' WITH 10 SX CEMENT. 4TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

 PLUGGING PROPOSAL RECEIVED BY STEVE MIDDLETON

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL PART NONE X

OPERATIONS COMPLETED: HOUR: 6:00 PM DAY: 01 MONTH: 06 YEAR: 2000

ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE

1ST PLUG AT 800' WITH 50 SX CEMENT. 2ND PLUG AT 270' WITH 50 SX CEMENT.

3RD PLUG AT 40' WITH 10 SX CEMENT. 4TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.

5TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.

7-3-00
RECEIVED
STATE CORPORATION COMMISSION

JUL 03 2000

REMARKS: USED 60/40 POZMIX 6% GEL BY ALLIED.

(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM)
I DID NOT OBSERVE THIS PLUGGING.

SIGNED [Signature]
(TECHNICIAN) FORM CP-2/3

DATE 7/5/00
W.M. NO. 1060006

CONSERVATION DIVISION
Wichita, Kansas
[Signature]