

2 040273

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 095-21494-0000

SW 1/4 SEC. 7, T. 27 S, R. 5 W/4

2970 feet from N/S section line

4950 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9917

Lease Name Krehbiel Well # 1

Operator: Luna Energy Corp.

County Kingman 94.87

Name & Address 11201 Dover Court

Well Total Depth 2919 feet

Yukon Oklahoma

Conductor Pipe: Size \_\_\_\_\_ feet

73099

Surface Casing: Size 8 3/8 feet 297

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well  D&A

Other well as hereinafter indicated

Plugging Contractor Gressel Oilfield Services License Number 5822

Address Burton KS.

Company to plug at: Hour: \_\_\_\_\_ Day: \_\_\_\_\_ Month: \_\_\_\_\_ Year: 19 \_\_\_\_\_

Plugging proposal received from Ed Gressel

(company name) above (phone) \_\_\_\_\_

were: \_\_\_\_\_

4 1/2 2919 Sand to 2755 @ 4 sks.

Perf. 2818-22 Set Bridge from 350 to 300'

fill with Redi-Mix

Plugging Proposal Received by W. Kirkpatrick (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part  None \_\_\_\_\_

Operations Completed: Hour: 1230 Day: 4 Month: 6 Year: 1986

ACTUAL PLUGGING REPORT Sand was dumped inside the 4 1/2" casing, 50' above the top perforation and capped with 4 sks of cement. The 4 1/2" was shot off and recovered 1850'. The Fluid level was at 370', a bridge was built from 370 to 300' and filled to the surface with Redi-Mix cement.

Remarks: Kingman Redi-Mix 6/11/86 (If additional description is necessary, use BACK of this form.)

INVOICED

DATE 6-10-86

INV. NO. 14084

RECEIVED STATE CORPORATION COMMISSION JUN 10 1986 6-10-86 CONSERVATION DIVISION WICHITA, KANSAS

Signed Ste. Ve. Gu (TECHNICIAN)

RP