

15-155-02676-0000

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely
Make Required Affidavit
Make or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bittling Building
Wichita, Kansas

OR

FORMATION PLUGGING RECORD

Strike out upper line
when reporting plugging
of formations.

RENO County. Sec. 27 Twp 23S Rge. 4W (E) SE 1/4 (W)

NORTH

Locate well correctly on above
Section Plat

Location as "NE 1/4 NW 1/4 SW 1/4" or footage from lines
 Lease Owner OLSON DRILLING COMPANY
 Lease Name M. QUERFELD Well No. 3
 Office Address PETROLEUM BLDG., TULSA, OKLA.
 Character of Well (completed as Oil, Gas or Dry Hole) OIL
 Date well completed UNKNOWN 1946
 Application for plugging filed SEPTEMBER 25TH 1946
 Application for plugging approved OCTOBER 1ST 1946
 Plugging commenced JANUARY 6TH 1947
 Plugging completed JANUARY 14TH 1947
 Reason for abandonment of well or producing formation DRY

If a producing well is abandoned, date of last production UNKNOWN 1946
 Was permission obtained from the Conservation Division or its agents before plugging was commenced? YES

Name of Conservation Agent who supervised plugging of this well MR. RUEL DURKEE
 Producing formation _____ Depth to top _____ Bottom _____ Total Depth of Well 3449' Feet.
 Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				13"	258'	LEFT IN
				7"	3449'	2700'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hold. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

DUMPED 6 SACKS OF CEMENT AT 3300'. SHOT PIPE OFF XXXXXX
AT 2700'. PULLED PIPE AND MUDDING HOLE TO 325'. DUMPED 25 SACKS OF CEMENT AT
325'. FINISHED MUDDING HOLE, AND PUT 10 SACKS OF CEMENT IN TOP OF SURFACE.

27 23 4W
70 43

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to HERMAN KAISER PIPE & SUPPLY COMPANY
 Address 819-20 PALACE BLDG., TULSA, OKLA.

STATE OF OKLAHOMA, COUNTY OF TULSA, SS.
BERTHOLD NEUWALD (employee of owner ~~XXXXXXXXXXXX~~) of the above-described well,
 being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Berthold Neuwald

819-20 PALACE BLDG., TULSA, OKLA.
 (Address)

SUBSCRIBED AND SWORN to before me this 30TH day of JANUARY, 19 47

My Commission Expires Nov. 3, 1950

My commission expires _____

Alfred L. ...
 Notary Public.

JAN 31 1947
 1-31-47

Olson Drilling Co.
M. Querfeld # 3
SE NE SE -27-23S-4W
Reno County, Kansas

15-135-02676-0000

0
149 Sand & Clay
258 Shale & Shells
425 Sand & Lime Shells
626 Shale & Shells
735 Lime & Shale
83 Lime
96 Red Bed
825 Lime
920 Lime & Shale
43 Lime & Red Bed
1367 Broken Lime
1690 Shale & Shells
1838 Shale
96 Broken Lime
1932 Shale & Shells
58 Shale
95 Broken Lime
2074 Shale & Shells
2103 Lime & Shale
86 Broken Lime
2260 Shale
2320 Lime
2439 Shale & Lime Shells
2526 Shale & Shells
54 Broken Lime
2828 Lime
37 Broken Lime
2907 Lime
16 Sandy Lime
57 Broken Lime
65 Lime
70 Shale
3011 Lime
31 Broken Lime
40 Shale
63 Lime
3106 Shale & Broken Lime
57 Shale
3209 Shale & Lime Shells
46 Var. Shale & Shells
55 Shells
3341 Chat
47 Chert
53 Chat
71 Soft Chat
81 Hard "
92 Chert
3402 Chat & Lime
3490 Lime
98 Broken Lime
3527 Shale
40 Lime, soft
3607 Shale
10 Sand

3612 Core (8" Lime Recovery)

RUST

3618 Lime 500' fluid in hole

top of chat 3255

Top of Lime 3609

Plugged back to 3540

Perforated with 61 holes from 3314 to 3334'

CASING RECORD

13" OD 40 # LW 256 ft.

7" OD 24# LW & EW 3414' 50 Sac Cement

27 23 4W
70 43

1-22-47
JAN 22 1947