

DISTRICT CONSERVATION AGENT'S REPORT

*R*

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. 34-18

LOCATION NE SW NW

SEC. 21 TWP. 24 RGE. 13W

Dry Hole \_\_\_\_\_ Abandoned Oil Well X Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 1 Lease R. J. Beckwith

Operator Standard Oil Co. Address 307 Ellsworth Kansas

Field \_\_\_\_\_ County Stafford

Total Depth 4067 Feet.

(Describe briefly the manner in which the well was plugged)

8 3/8" 282' lined with 100% cement.  
5 1/2" 4057' cemented with 100% cement  
Plug Back Baker Plug 3775' Prepacked  
3738' to 3742' and 3707' to 3714' filled with  
sand to 3700' run 5% cement with dummy  
failer mud to 270' set rock bridge run 20%  
cement mud to 35' set rock bridge run  
10% cement col. Pipe Pulling 9 mi. cont's  
*John Riggs J.P.*

**PLUGGING**  
FILE NO. 21-24-13W  
BOOK PAGE 24 LINE 18  
STATE CORPORATION COMMISSION

8-28-52 M. C. Rivers  
District Conservation Agent

Date 8-26-52

AUG 23 1952

CONSERVATION DIVISION  
Wichita, Kansas