

15-185-10453-0000

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bittling Building
Wichita, Kansas

Stafford County, Sec. 27 Twp. 24 Rge. 13 (E) ^W ~~E~~ ~~W~~

Location as "NE/CNW/SW" or footage from lines C NE NW NE

Lease Owner The Atlantic Refining Company

Lease Name Pounds Well No. 1

Office Address P. O. Box 17, Great Bend, Kansas

Character of Well (completed as Oil, Gas or Dry Hole) Oil well converted to SWD.

Date well completed As salt water disposal 4-20 19 54

Application for plugging filed 12-31 19 53

Application for plugging approved 1-1 19 54

Plugging commenced 3-4 19 54

Plugging completed 3-13 19 54

Reason for abandonment of well or producing formation salt water disposal well

If a producing well is abandoned, date of last production _____ 19 _____

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes.

Name of Conservation Agent who supervised plugging of this well Mr. M. A. Rives

Producing formation _____ Depth to top _____ Bottom _____ Total Depth of Well 4612 PB Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				12 1/2"	246'	0
				7"	4111'	0
				5 1/2"	3168'	0

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Pump down 7" casing 250 sacks regular cement + 4% Gel, 250 sacks regular cement + 300# calcium chloride. Went in on vacuum. Let set from March 4 to March 6. State checked and found cement at 56' down in 7" casing. Run 12 sacks cement and filled 7" to top. Then on March 13, pumped 7 sacks between 12 1/2" casing and 7" casing to fill the space between the two strings of casing.
P&A.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor Halliburton Oil Well Cementing Co. mix cement.

Address S. K. Myers supervised same. Box 17, Great Bend, Kansas

STATE OF Kansas, COUNTY OF Barton, ss.

Stanton K. Myers (employee of owner) or (~~owner or operator~~) of the above-described

well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Stanton K. Myers
P. O. Box 17, Great Bend, Kansas
(Address)

SUBSCRIBED AND SWORN TO before me this 17 day of March, 19 54

My commission expires 7-18-55

W. B. Bradshaw
Notary Public.

PLUGGING
FILE SEC 27 T 24 R 13 W
PAGE 4 LINE 34

24-7566-5 3-53-20M

3-18-1954
CONSERVATION DIVISION
WICHITA, KANSAS

DEEPENING FOR
SALT WATER DISPOSAL

WELL RECORD

15-185-10453-0000

Block or Twp. 24S-13W
 Lease Pound
 Lease No KS-2600
 County Stafford
 Well No. 1
 State Kansas
 Location C NE NW NE of 27-24S-13W
 Elevation 1,927 Feet

Drilled { Contract
 { Company Tools
 Contracted Depth
 Completed Depth
 Feet
 Feet
 Date { Started
 { Completed
 { Deepened 4-7-45
 { Cleaned Out

Name of Contractor Parker Drilling Company
 Contract Price Per Foot Day Work
 Well Estimated Cost Method of Drilling Rotary
 Well Actual Cost

BEFORE SHOOTING

AFTER SHOOTING

Initial Production Flowing Initial Production Flowing
 Settled Production on Pump Settled Production on Pump
 Baume Test Water With Oil %

Casing Record			Torpedo Record					
SIZE	SET	PULLED	Date Company	From	To	Feet	Size of Shell	Total Qts.

OLD TOTAL DEPTH 4,121 TD
 3,576 PBD
 DEEPENING Started: 3-6-45. Completed: 4-7-45

FORMATION	TOP	BOTTOM
Sand	3,576	3,586
Sand and junk	3,586	3,598
Crushed rock and junk	3,598	3,630
Crushed rock	3,630	3,780
Crushed rock	3,780	4,123
Lime	4,123	4332
Chert and lime	4332	4,335
Lime and chert	4,335	4,340
Sand	4,340	4,354
Lime	4,354	4,365
Correction, Total Depth		4,363
Bear shoe and cement	4,349'9"	4,363
Lime	4,363	4,423
Sandy lime and shale	4,423	4,526
Sand and lime	4,526	4,547
Lime	4,547	4,612 TD

*3558 Top Line
 4348 Bottom*

*Rec'd
 3-18-54*

Cemented 790' of 5 1/2" liner at 4,348' with 65 sax cement. (3,569 - 4,348')
 Circulated out 3 sax cement.
 Drilled out to 4,612' and found top of granite at 4,610'.
 Acidized with 6,000 gallons.
 Pumped 244 bbls. water per hour.
 Were unable to catch up with vacuum on well.

PRESENT TOTAL DEPTH: 4,612'

PLUGGING
 FILE SEC 27 T 24 R 13W
 BOOK PAGE 4 LINE 24