INV. NO.

, , , , , , , , , , , , , , , , , , ,	API NUMBER 15- 185-22, 157 -000
To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTIONC S/	2 SW NW , SEC. 29 , T 24 S, R 14 W/K
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	
TECHNICIAN'S PLUGGING REPORT	4620 feet from M/E section line
Operator License #5087	Lease Name DeBusk Well / 1-29
Operator: Texas Energies, Inc.	County Stafford 144.30
Name& P. O. Box 947	Well Total Depth 4440 feet
Pratt, KS 67124	Conductor Pipe: Size feet /
	Surface Casing: Size 8 5/8 feet 349
Abandoned Oll Well Gas Well	nput WellD&A
Other welt as hereinafter indicated	
Plugging Contractor Wheatstate Oilfield Serv	
Address P. O. Box 329, Pratt, KS 67124	
Company to plug at: Hour: 2:00 pm Day: 4	Month: April Year:19 85
Plugging proposal received from To	· · · · · · · · · · · · · · · · · · ·
(company name) Wheatstate	
•	ement_through_drill_pipe
1st plug at 1420' with 50 sx cement	
2nd plug at 710' with 40 sx cement	
3rd plug at '400' with 40 sx cement	·
solid bridge 4th plug hulls - plug at 40' cement to su	urface with 10 sx cement
6th plug to circulate rat hole with 15 sx co	ement I Received by Slyse Lesley (TECHNICIAN)
	(TECHNICIAN)
Plugging Operations attended by Agent?: All	PartNoneX
Operations Completed: Hour: 4:15 pm Day: 4	Month: April Year:19 85
ACTUAL PLUGGING REPORT 1st plug at 1420' wit	th 50 sx cement, 2nd plug at 710' with 40
sx cement, 3rd plug at 400' with 40 sx cemen	nt, 4th & 5th plugs - solid bridge - hulls -
plug at 40' cement to surface with 10 sx	cement, 6th plug to circulate rat hole with
15 sx cement,	RECEIVED
	CTATE CORPORATION COMMISS
	4-12-1985 APR 1 2 1985
Remarks: Used 60/40 Pozmix 2% gel 3% cc by Do	
- · ^ F N	ecessary, use BACK of this form.) Holma Kansus
(dil not) observe this plugging.	
4-18-8	Signed (TECHNICIAN)

FORM CP-2/3 Rev.01-84