

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date January 10, 1987 month day year

API Number 15- 185-22,404-0000

OPERATOR: License # 5418
Name ALLEN DRILLING COMPANY
Address P.O. Box 1389
City/State/Zip Great Bend, KS 67530
Contact Person Doug Hoisington
Phone (316) 793-5877

S/E NW SW Sec. 17 Twp. 24 S, Rg. 13
1650 Ft. from South Line of Section
4590 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5418
Name ALLEN DRILLING COMPANY
City/State Great Bend, KS

Nearest lease or unit boundary line 330 feet
County Stafford
Lease Name HARRISON Well # 1-17
Ground surface elevation 1930 (estimated) feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 100'
Depth to bottom of usable water 250'
Surface pipe by Alternate 1 X 2
Surface pipe planned to be set 810'
Conductor pipe required none
Projected Total Depth 4225 feet
Formation Arbuckle

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj X Pool Ext Air Rotary
OWWO Expl Wildcat Cable

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications
Date 12/22/86 Signature of Operator or Agent Title Exploration Mgr

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt.
This Authorization Expires 6-23-87 Approved By 12-23-86

Handwritten notes: 11/26/86, 7 ft at 815 ft, etc.

Sec. Twp. S, Rg. East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ Top of Arbuckle feet depth with 20 30 SXS of 60/40 poz. 6% gel
2nd plug @ 810' feet depth with 80 SXS of 60/40 poz. 6% gel
3rd plug @ 400' feet depth with 80 SXS of 60/40 poz. 6% gel
4th plug @ 40' feet depth with 10 SXS of 60/40 poz. 6% gel
5th plug @ feet depth with SXS of
(2) Rathole with 15 SXS (b) Mousehole with SXS

Table with columns: PUSHER, TD, SURFACE PIPE @, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @ FT. W/ SX, 2nd PLUG @ FT. W/ SX, 3rd PLUG @ FT. W/ SX, 4th PLUG @ FT. W/ SX, RAT HOLE CIRCULATED W/ SX, MOUSE HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ SX, CEMENT COMPANY, TECHNICIAN

1-6-87
STATE CORPORATION COMMISSION
JAN 6 1987
CONSERVATION DIVISION
Wichita, Kansas