1 EO NT Waster Cha 1/11/1	المخضار ٢٥	1121036 6-	6 API NUMBER 15-	185 <b>-</b> 01 <b>,</b> 036 <b>→</b>	0000
perator License \$ 5097    County Stafford   Stafford   Stafford   Stafford	CONSERVAT	TION DIVISION - PLUGGING SECTION RADO DERBY BUILDING			
Martin Oil Producers, Inc.    County Stafford	TECHNICIA	AN'S PLUGGING REPORT	4950	feet from	E section lin
County Stafford    Main   Stafford   Staffor	)perator	License # 5097	Lease Name Mor	ris W	A-1
Meli Total Depth   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280   139,10   4280		Martin Oil Producers, Inc.	County Staffor	d	
Surface Casing: Size   feet   Surface Casing: Size   Size   530   Subandoned Oil Well   X   Gas Well   Input Well   SWD Well   D&A   Deter well as hereinafter Indicated   Plugging Contractor   Mike's Testing & Salvage Inc.   License Number   31529   Address   P.O. Box 209, Chase, KS 67524   Company to plug at: Hour: 5:30 p.m. Day:   6   Month:   6   Year: 19 95   Plugging proposal received from   Manny   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing & Salvage Inc.   (phone)   316-938-294   (company name)   Mike's Testing	Name& Address		Weil Total Dep	th4280	139.10
Actual Plugging Operations attended by Agent?: All X Part None  Plugging Operations Completed: Hour: 7 p.m. Day: 6 North: 6 Year:1995  Actual Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 7 p.m. Day: 6 North: 6 Year:1995  Actual Plugging Report 1st plug sanded back to 3970' and dumped 4 sx cement on top of sx through bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, release 8 5/8" wiper plug and pumped 4 sx cement on top of sx Actual Plugging Report 1st plug sanded back to 3970' and dumped 4 sx cement on top of sx Actual Plugging Report 1st plug sanded back to 3970' and dumped 4 sx cement on top of sx through bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 50 sx cement on top of sx through bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  11 Sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  12 Signed Dawn Pluggling.  13 Signed Dawn Pluggling.  14 3 9 8 7 Signed Dawn Pluggling.  15 Signed Dawn Pluggling.  16 Signed Dawn Pluggling.  17 Signed Dawn Pluggling.		Wichita, KS 67202			
Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 5:30 p.m. Day: 6			Surface Casing	: \$1ze 8 5/8	feet530
Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 5:30 p.m. Day: 6	handone	d Oli Well X Gas Well	Input Well	SWD Well	A&O
Plugging proposal received from Manny  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-294.  Were: 42" at 4280' w/160 sx cement, PBTD 4140', Perfs at 4173-77, 4021-24'  1st plug sand back to 3970' and dump 4 sx cement on top of sand through bailer,  2nd plug pump into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 gel, 100 lbs. hulls, release 8 5/8" wiper plug and pump 100 sx cement.  Plugging Proposal Received by Duane Rankin (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year: 1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 42" casing with form.)  A 2877  Signed Deace Leading (TECHNICIAN)  Signed Deace Leading (TECHNICIAN)			lvage Inc.	License Nu	31529
Mike's Testing & Salvage Inc.  (phone) 316-938-294  vere: 4½" at 4280' w/160 sx cement, PBTD 4140', Perfs at 4173-77, 4021-24'  1st plug sand back to 3970' and dump 4 sx cement on top of sand through bailer,  2nd plug pump into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10  gel, 100 lbs. hulls, release 8 5/8" wiper plug and pump 100 sx cement.  Plugging Proposal Received by			6 Month:		Year:19 <u>95</u>
Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year: 1995 ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement.  Dischard plug pumped into 8 5/8" surface casing with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 makes through bailer,  Plugging Proposal Received by Duane Rankin (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year: 1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer, 2nd plug pumped into 8 5/8" surface casing with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 1bs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  We gel 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing the same observe this plugging.  Signed Duan Cauthair (TECHNICIAN)			Inc.	(pho	ne) 316-938-2943
Ist plug sand back to 3970' and dump 4 sx cement on top of sand through bailer,  2nd plug pump into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 gel, 100 lbs. hulls, release 8 5/8" wiper plug and pump 100 sx cement.  Plugging Proposal Received by  Duane Rankin  (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year:1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  What is additional description is necessary, use BACK of this form.)  Signed Duane Cashing.  Cashing	•		**		
2nd plug pump into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 gel, 100 lbs. hulls, release 8 5/8" wiper plug and pump 100 sx cement.  Plugging Proposal Received by  Duane Rankin  (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year:1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of st through bailer, 2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks:  Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing the standard observe this plugging.  Signed Danne Rankin  TECHNICIAN)  Signed Danne Rankin  TECHNICIAN)  Signed Danne Rankin  TECHNICIAN)  Signed Danne Rankin  TECHNICIAN)					<del></del>
Plugging Proposal Received by Duane Rankin  (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour: 7 p.m. Day: 6 Honth: 6 Year:1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of st through bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx sel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks:  Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.  (If additional description is necessary, use BACK of this form.)  Notation observe this plugging.  Signed Dann Caulling  (TECHNICIAN)	2nd plug	pump into 8 5/8" surface casing	with 300 lbs. hulls,	10 sx gel, 5	0 sx cement, 10
Plugging Proposal Received by    Duane Rankin (TECHNICIAN)			.•		
Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour; 7 p.m. Day: 6 Month: 6 Year:1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx sel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  What is a selection of this form.)  (if additional description is necessary, use BACK of this form.)  Note that the selection of the selecti			·		
Plugging Operations attended by Agent?: All X Part None  Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year:1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.  (If additional description is necessary, use BACK of this form.)  Note that the same of the standard		Pingaina Pi	conosal Received by	Duane	Rankin
Operations Completed: Hour: 7 p.m. Day: 6 Month: 6 Year: 1995  ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.				(TE	CHNICIAN)
ACTUAL PLUGGING REPORT 1st plug sanded back to 3970' and dumped 4 sx cement on top of sathrough bailer,  2nd plug pumped into 8 5/8" surface casing with 300 1bs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 1bs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks:  Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.  (If additional description is necessary, use BACK of this form.)  N. Mail Additional description is necessary, use BACK of this form.)  Signed Duan Rendering  (TECHNICIAN)	Pluggin	g Operations attended by Agent?:	All X Par	† <u> </u>	None
through bailer,  2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42    (If additional description is necessary, use BACK of this form.)    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   12 - 42      Used 60/40 Pozmix 6% gel by Allied. Reco	•				
2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,  10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Remarks:  Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing.  (If additional description is necessary, use BACK of this form.)  N. Mail Additional observe this plugging.  Signed Duan Caulain  (TECHNICIAN)	ACTUAL	PLUGGING REPORT 1st plug sanded	back to 3970 and du	mped 4 sx cem	ent on top of sa
10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 0-600 psi and shut in 200 psi.  Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing and pumped 100 sx cement.  (If additional description is necessary, use BACK of this form.)  Notation observe this plugging.  L-23-95  Signed Duan Caulain  (TECHNICIAN)	through	bailer,		·	
Maximum pressure 0-600 psi and shut in 200 psi.    Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 4½" casing   Companies	2nd plug	pumped into 8 5/8" surface casin	g with 300 lbs. hull	s, 10 sx gel,	50 sx cement,
Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 42" casing (12 - 12 - 9)  (If additional description is necessary, use BACK of this form.)  N. Mail Advances observe this plugging.  Le-23-95  Signed Duan Caulain (TECHNICIAN)	10 sx ge	1, 100 lbs. hulls, released 8 5/8	" wiper plug and pum	ped 100 sx ce	ment. And D
(if additional description is necessary, use BACK of this form.)  N. Wall Advances observe this plugging.  Signed Duan Caukin  (TECHNICIAN)	Maximum	pressure 0-600 psi and shut in 20	0 psi.	V	My 2 9 1188104
(if additional description is necessary, use BACK of this form.)  N. Wall Advances observe this plugging.  Signed Duan Caukin  (TECHNICIAN)	<u></u>			GUIVO SAV.	1995
(if additional description is necessary, use BACK of this form.)  N. Wall Advances observe this plugging.  Signed Duan Caukin  (TECHNICIAN)		Used 60/40 Pozmix 6% gel by All	ied. Recovered 2500	of 4½" casi	1/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2
E 6-23-95 Signed Dans Kenkin (TECHNICIAN)	Remarks	(if additional description	is necessary, use E	MACK of this	form.)
E 6-23-95 Signed Dans Kenkin (TECHNICIAN)	N.W.O	decomposition observe this plugging	· ~		
43981	· 6-		/ /	can Caul	kin
	W W	2987		( ) ECHN (C)	vul

FORM CP-2/3 Rev.01-84