

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging of formations.

~~SE SW SE~~ Reno Co County. Sec 11 Twp. 23S Rge. 4W (E) (W)

Location as "NE 1/4 NW 1/4 SW 1/4" or footage from lines SE SW SE

Lease Owner THE BARNSDALL OIL COMPANY

Lease Name M. Sabin Well No. C-7

Office Address Box 2039, Tulsa, Okla.

Character of Well (completed as Oil, Gas or Dry Hole) Oil Well

Date, well completed Feb. 6th, 1935 19

Application for plugging filed July 31st, 1941 19

Application for plugging approved August 2nd, 1941 19

Plugging Commenced August 8th, 1941 19

Plugging Completed August 11th, 1941 19

Reason for abandonment of well or producing formation

Not producing in paying quantities

If a producing well is abandoned, date of last production April 11th, 1937 19

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Ruel Durkee, McPherson, Kans

Producing formation Hunton Lime Depth to top 3588 Bottom 3606 Total Depth of Well 3606 Feet

Show depth and thickness of all water, oil and gas formations.


OIL, GAS OR WATER RECORDS

CASING RECORD

| Formation | Content | From | To | Size | Put In | Pulled Out |
|-------------|---------|------|------|--------|----------|------------|
| Hunton Lime | Oil | 3588 | 3606 | 16" | 153.95' | None |
| | | | | 13" | 593.68' | 77' 9" |
| | | | | 8-5/8" | 3583.73' | 3113' 6" |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Hole filled with crushed rock from 3606 to 3587. Six sack cement plug set at 3587' and hole filled with heavy mud from top of plug to 3250'. Six sack cement plug set at 3250' and hole filled with heavy mud from top of plug to 200'. Fifteen sack cement plug set at 200' and hole filled with heavy mud from top of plug to cellar base. Hole capped with 10 sacks cement.



PLUGGING
FILE 15-155-02784-0000
BOOK PAGE 1 LINE 14

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to The Barnsdall Oil Company
Address Box 2039, Tulsa, Okla.

STATE OF Oklahoma, COUNTY OF Tulsa, ss.
G. B. HUGHES (employee or owner) or (operator) of the above-described well,

being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) *[Signature]*

BARNSDALL OIL CO., BOX 2039, Tulsa, Okla.
(Address)

SUBSCRIBED AND SWORN to before me this 26 day of August 19 41

My commission expires 7-22-43

[Signature]
Notary Public.

WELL LOG - M. SABIN C-7

LOCATION:

220' N & 990' E of SW Corner of lease,
SE/4, Section 11-23S-4W, Reno County, Kans

15-155-02784-0000

CASING RECORD:

| | | | |
|------------------------|----------|----------|---------------------------------------|
| 16" OD 70# 8 Thd. LW | 8 Jts. | 153' 11" | Set at 161.95' with 225 Sacks Cement |
| 13" OD 50# 8 Thd. LW | 29 Jts. | 593.68' | Set at 599.60' with 250 Sacks Cement |
| 8 5/8" OD 28# 8 thd SS | 122 Jts. | 3583.73' | Set at 3582.45' with 100 Sacks Cement |

FORMATION RECORD:

| | | | | | |
|-----------------------|------|------|-------------------------|---------|---------|
| Sand & Shale | 0 | 162 | Broken Lime | 2500 | 2532 |
| Surface sand & Shells | 162 | 525 | Lime | 2532 | 2675 |
| Lime & Shale | 525 | 832 | Sandy Lime | 2675 | 2768 |
| Lime | 832 | 895 | Lime | 2768 | 2847 |
| Shale & Lime | 895 | 1000 | Broken Lime | 2847 | 2892 |
| Shale | 1000 | 1112 | Lime | 2892 | 2950 |
| Lime & Shale | 1112 | 1206 | Lime & Shale | 2950 | 2972 |
| Lime & Shells | 1206 | 1300 | Lime | 2972 | 2996 |
| Shale & Lime Shells | 1300 | 1410 | Shale | 2996 | 3037 |
| Shale | 1410 | 1615 | Shale & Lime | 3037 | 3064 |
| Lime | 1615 | 1640 | Shale | 3064 | 3258 |
| Shale & Lime | 1640 | 1766 | Chat | 3258 | 3470 |
| Shale | 1766 | 1857 | Lime & Shale | 3470 | 3502 |
| Shale & Lime Shells | 1857 | 1898 | Shale | 3502 | 3581.55 |
| Shale | 1898 | 1957 | | | |
| Broken Lime & Shale | 1957 | 2005 | <u>CORED:</u> | | |
| Lime | 2005 | 2041 | Gray Shale | 3581.55 | 3585.55 |
| Lime & Shale | 2041 | 2175 | Brown Shale | 3585.55 | 3588.55 |
| Lime | 2175 | 2260 | Hard White, Crystalline | | |
| Broken Shale & Lime | 2260 | 2315 | lime, some Saturation | 3588.55 | 3594.55 |
| Lime | 2315 | 2340 | | | |
| Shale | 2340 | 2350 | <u>CABLE TOOLS:</u> | | |
| Lime | 2350 | 2380 | Hunton Lime | 3595 | 3605 |
| Shale | 2380 | 2500 | | | |

PLUGGING
FILE SEC---T---R---
BOOK PAGE---LINE---

RECEIVED
AUG 12 1941
STATE CORP. COMM.
CONSERV. DIV.