OCT 1.5 2001

Kansas Corporation Commission OIL & GAS CONSERVATION DIVISION

Form ACO-1 September 1999 Form Must Be Typed

WELL COMPLETION FORM WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

ODIOINIAI

Operator: License #_6477	API No. 15 - 095-21778-0000 URIGINAL
Kach Bindings	County: Kingman
P O Roy 20	SWISWISWI1/4 Sec. 33 Twp. 27 S. R. 5 East V West
Address: 1.0.Box 29 City/State/Zip: Medford, Ok 73759	55 feet from (\$) / N (circle one) Line of Section
Purchaser:	70 feet from E /(W) (circle one) Line of Section
Operator Contact Person: Kip Swaggart	Footages Calculated from Nearest Outside Section Corner:
Phone: (580) 395-6274	(circle one) NE SE NW (SW)
Contractor: Name: Triangle C.P. Company	Lease Name: Rectifier N-13 Well #:
License: 31710	Field Name: Rectifier N-13
Wellsite Geologist:	Producing Formation:
Designate Type of Completion:	Elevation: Ground: Kelly Bushing:
New Well Re-Entry Workover	Total Depth: 250 Plug Back Total Depth:
Oil SWD SIOW Temp. Abd.	Amount of Surface Pipe Set and Cemented at 80 Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used? ✓ Yes ☐ No
Dry Other (Core, WSW, Expl., Cathodic, etc)	if yes, show depth set 5, 40, 75
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from
Operator:	feet depth tow/sx cmt.
Well Name:	hu w lil O i an
Original Comp. Date: Original Total Depth:	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	Chloride content N/A ppm Fluid volume 75 bbls
Plug Back Plug Back Total Depth	Dewatering method used Tank truck / back filled
Commingled Docket No	
Dual Completion Docket No	Location of fluid disposal if hauled offsite:
Other (SWD or Enhr.?) Docket No	Operator Name:
06/15/2001 06/16/2001 06/17/2001	Lease Name: License No.:
06/15/2001 06/16/2001 06/17/2001 Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R
Recompletion Date Recompletion Date	County: Docket No.:
Kansas 67202, within 120 days of the spud date, recompletion, workov Information of side two of this form will be held confidential for a period of	h the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, ver or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. 12 months if requested in writing and submitted with the form (see rule 82-3-s and geologist well report shall be attached with this form. ALL CEMENTING s. Submit CP-111 form with all temporarily abandoned wells.
All requirements of the statutes, rules and regulations promulgated to regulaterin are complete and correct to the best of my knowledge.	late the oil and gas industry have been fully complied with and the statements
Signature: Rep Junggart	KCC Office Use ONLY
Title: Corrosion Cechnician Date: 10/12/01	Letter of Confidentiality Attached
Subscribed and sworn to before me this 12th day of October	If Denied, Yes Date:
10 20D1	Wireline Log Received
\mathcal{L}	Geologist Report Received
Notary Public: Office R. Wolfing	UIC Distribution
Date Commission Expires: 100. 13,2004	

Side Two

15-095-21778-05-00 ORIGINAL

Operator Name: Koch	n Pipelines		Lease	e Name: <u>-</u> ł	Rectifier N-1	3	Well #:	
Sec. 33 Twp. 27	7 S. R. <u>5</u>	_	Count	ty: King	man			
ested, time tool open emperature, fluid reco	and closed, flowin	and base of formations og and shut-in pressure es if gas to surface tes final geological well si	es, whether s st, along with	shut-in pre	ssure reached	static level, hydr	ostatic pressure	es, bottom hole
Orill Stem Tests Taken (Attach Additional S		Yes No			og Formati	on (Top), Depth	and Datum	☐ Sample
Samples Sent to Geol	ogical Survey	☐ Yes ☐ No	,	Nam	е		Тор	Datum
Cores Taken	,	Yes No			pull from	CEIVED	ľ	
Electric Log Run (Submit Copy)		☐ Yes ☐ No			-	15200		
ist All E. Logs Run:					UU	1 1 2 Nia		
					KC	CMICHITA	N.	
_								
		CASIN Report all strings s	NG RECORD set-conductor, s		_	tion, etc.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)		eight s. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Water formation	16"	10"	40		80	Neat	60	
		ADDITION	IAL OF MENT		FF75 D500D5			
Purpose:	Depth Top Bottom	Type of Cement		#Sacks Used Type and Percent Additives				
Protect Casing Plug Back TD Plug Off Zone								
Shots Per Foot	PERFORAT	ION RECORD - Bridge F	Plugs Set/Type	e	Acid, Fra	cture, Shot, Cemer	nt Squeeze Recor	
Shots Per Pool		Footage of Each Interval		·		mount and Kind of M		Depth
TUBING RECORD	Size	Set At	Packer /	At	Liner Run	Yes No		
Date of First, Resumed F	roduction, SWD or E	nhr. Producing M	1ethod	Flowing	J Pumpi	ng Gas Li	ift Othe	er (Explain)
Estimated Production Per 24 Hours	Oil	Bbls. Gas	Mcf	Wate	er B	bls.	Gas-Oil Ratio	Gravity
Disposition of Gas	METHOD OF	COMPLETION			Production Inter	rval		
Estimated Production Per 24 Hours Disposition of Gas Vented Sold (If vented, Sun	METHOD OF						Gas-Oil Ratio	

RECEIVED

ORIGINAL

TRIANGLE C.P. COMPANY **CATHODIC PROTECTION**

OCT 1.5 2001

KCC MICHITA

SERVICE

COMPANY Koch Hydrocarbon Company

15-095-21778-0000 CITY/STATE Chney, KS reguliernuwer nab

PROTECTED STRUCTURE P/L

DRILLER Triangle C. P. Company

JOB NUMBER 01CD670 DATE

06/17/1901

TESTING VOLTAGE

	ELECTRIC LOG						
DEPTH	DRILLERS LOG	ANODE #	NATIVE	W/O COKE	W/COKE		
FEET	0' - 80' - Casing						
	0' - 20' - sand						
10							
20	20' - 60' - shale						
30							
					· · · · · ·		
40					:		
50							
			•	· · · · · · · · · · · · · · · · · · ·			
60	60' - 80' - gray clay						
70							
							
80	80' - 110' - shale		, ,	:			
			3.9	· · · · · · · · · · · · · · · · · · ·			
90	See P. Seeting on J. Cappe Co., Contract of the Co.		3.7	7.1	, , , ,		
			3.5				
100			3.5				
	· · · · · · · · · · · · · · · · · · ·	·	3.5				
110	110' - 120' - gyp rock		3.5				
	ine ine gypreek		4.1				
120	120' - 140' - gray shale &	**	5.8	-			
	gyp rock		6.2				
130	gyproun		6.5				
			6.4				
140	140' - 230' - red shale		7.1				
			7.9				
150			8.4	-,			
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		8.3				
160	A STATE OF THE PARTY OF THE PAR	10	7.5	7.5	11.5		
			8.4		1		
170		9	8.1	8.1	12.1		
1,7.0			7.6	<u> </u>	12.1		
180		8	7.3	7.3	11.1		
100			6.5	1.5	11.1		
190	1	7	7.4	7.4	11.2		
1.80			7.4	1.4	11.2		
200				0.4	40.4		
. 200	A A A A A A A A A A A A A A A A A A A	6	8.1	8.1	12.1		
240	1		7.7	7.1			
210	<u> </u>	5	7.1	7.1	11.2		

TRIANGLE C.P. COMPANY CATHODIC PROTECTION

SERVICE

SERVICE			
COMPANY Koch Hydrocarbon Cor	npany	Chystria	Giney, KS
PROTECTED STRUCTURE	PL	RECTIFIER NUME	ER N-13
DEPTH 250°	DIAMETER 10"	JOB NUMBER	01CD670
DRILLER Triangle C. P. Company		DATIE	06/17/1901
TESTING VOLTAGE	i di	volts COUNTY	Kingman

DRILLERS LOG			ELECTRIC LOG				
220	DEPTH		ANODE #	NATIVE	W/O COKE	W/COKE	
220	FEET	0' - 80' - Casing					
220				6.8			
230 230' - 250' - gray shale 3 5.4 5.4 10.1 240 2 6.7 6.9 10.8 250 1 7.1 7.1 11.1 260 RECEIVED 270 OCT 1-5 Spril 290 300 310 320 330 340 350 360 370 380 390	220		4	5.7	5.7	10.4	
230 230' - 250' - gray shale 3 5.4 5.4 10.1 240 2 6.7 6.9 10.8 250 1 7.1 7.1 11.1 260 007 1 5 900 200 200 200 200 200 200 200 200 200							
240	230	230' - 250' - gray shale	3		5.4	10.1	
240	200	200 - 200 gray share			0.4	10.1	
250	240		2		6.0	10.8	
250	240				0.9	10.0	
260 RECEIVED 270 OCT 1-5 2001 280 RECEIVED 290 300 310 320 330 340 350 360 370 380 390	250	ļ			7.1	11.1	
270 OOT 1-5 POOT 280 KCC WACHETA 290 300 310 320 330 340 350 360 370 380	250			7.1		11.1	
270 OOT 1-5 POOT 280 KCC WACHETA 290 300 310 320 330 340 350 360 370 380	000						
280 KCC WICHT 290 300 310 320 330 340 350 360 370 380	260		–				
280 KCC WICHT 290 300 310 320 330 340 350 360 370 380		007 1.5 2001					
290 300 310 320 330 340 350 360 370 380 390	270						
290 300 310 320 330 340 350 360 370 380 390			.				
300 310 320 330 340 350 360 370 380	280	KORTHAN					
300 310 320 330 340 350 360 370 380							
310 320 330 330 340 350 360 370 380 390 390	290						
310 320 330 330 340 350 360 370 380 390 390							
310 320 330 330 340 350 360 370 380 390 390	300		:				
320 330 340 350 360 370 380				···· <u>·</u>			
320 330 340 350 360 370 380	310						
330 340 350 360 370 380 390							
330 340 350 360 370 380 390	320						
340 350 360 370 380 390	020			_			
340 350 360 370 380 390	330					·	
350 360 370 380 390	330						
350 360 370 380 390	240						
360 370 380 390	340						
360 370 380 390	250						
370 380 390	350						
370 380 390	000	 					
380	360						
380							
390	370						
390						.	
	380						
400	390						
400							
400	400						

WORK TICKET




P.O. 8ox 2284 Gillette, WY 82717-1662 Office and Fax: (307) 662-1689 Mobile: (307) 689-1823

ENT'D JUN 29 2001

P.O. Box 220 • Crescent, OK 73028

Lease Char	y KS		Job 7	#01c	6	670 Da	e _ 6 -	16-	01		
Well No. 13	•		Custome P.O. No.				ntractor				
				WOR	ΚPI	ERFORMED	·· ·	A. v			
INSTAIL	de	es ·	Govi	vd B	<u> </u>	Pipel	inc	2,2	رن ن		
ALL FIT		,		hook		F (*					-
3/4 90'											
Recti Fer	4	Wee/	1 Box	NAS_	256	OFT 10:N	The Contract of Co	VED			
		Za	o y -	125							
			Γ Γ οΝ-	1259			OCT 1	2001			
						К	CC MI	CHITA			
				1-125							
		ERN	CST	- 125			1			· · · · · · · · · · · · · · · · · · ·	
Employees ²	Time	Hours	Rate	Amou	nt	Equipment	Unit#	Hours	Rate	Amou	nt
						Trencher					
						1 Ton w/tools					
						Backhoe					
						Trailer					
					_	Generator/Welder	,		L		
TOTALS					Ĺ.,	Tractor w/attachments	<u> </u>			<u> </u>	
Materials Use	d			Amou							_
Hole plug				76 b49	2/2						↓_
CEMENT			\Rightarrow	5060	4	TOTAL					<u> </u>
ANDOES - VE	NT - J-	BOX		15eT	1	1					
V_1:N		····		220	*	h)	CT 43401	INIT			
10in (SL	h 40 y			80'	1	TOTAL TICK	EIAMO	JN I			
	DER SA	acks		3	8 }-						
3/4 Flex	<u></u>			14	彩						
TOTAL						j ,					
				•							
Approved						Approved					
			For Car	itractor	_				For	Customer	

TRIANGLE C.P. COMPANY



ORIGINAL Invoice

DATE

INVOICE #

6/25/2001

01-2926

BILL TO:

Koch Hydrocarbon Company Attention: Mr. Kip Swaggart P.O. Box 29 Medford, OK 73759

RECEIVED

OCT 15 2001

KCC MICHITA

P.O. NUMBER	TERMS	PROJECT
AFE#30028	Due on receipt	01CD670

QUANTITY	DESCRIPTION		RATE	AMOUNT
	Rectifier Number N-13 Kingman County, Cheney, KS			
250	Drilling Services (10")		12.00	3,000:00
	All-labor, equipment, fuel, lodging and per diem to load ar groundbed to new rectifier.	nd hookup deepwell	5,055.00	5,055.00
and the same of th	All Labor & equipment to set and cement casing, per foot. Feet, 1" PVC Pipe Schedule 40		19.00 0.25	1,520.00 5.00T
80	10" PVC Casing		6.00	480.00T
。 A、25 m、35 pp. 1-411 PS 54 pp. 15 p	10" Schedule 40 T 10" PVC Casing Cap		331.00 72,00	72.00T
a a begin way to that between me and you are all the	10" X 6" PVC Schedule 40 SXS Bushing 6" X 4" PVC SXS Schedule 40 Bushing		123.00 13.00	123.00T 13.00T
	4" PVC 160 # Casing 4" PVC, Schedule 40 Elbow		1.20	48.00T 9,00T
Long the following the long of the latest and the l	4" PVC, Schedule 40 T 4" X 2" PVC, Schedule 40, S X S Bushing		12.80 5.20	12.80T 10.40T
	2" X 1" PVC SXS Bushing Kansas State Tax		0.80 4.90%	0.80T 54.15

It's been a pleasure working with you!

TOTAL

\$10,734.15