15-185-12535-0000

STATE OF KANSAS
STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

WELL PLUGGING RECORD
OR
FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging off formations.

NORTH

Locate well correctly on above Section Plat

Stafford County. Sec. 9 Twp. 24 Rge. (E) 11 (W)

Location as "NE¼NW¼SW¼" or footage from lines SW¼-NE¼-NE¼

Lease Owner Champlin Refining Company

Lease Name Figger Well No. 4

Office Address P. O. Drawer #552, Enid, Oklahoma.

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date well completed September 19 41

Application for plugging filed May 27, 19 48

Application for plugging approved (Verbal) May 18, 19 48

Plugging commenced May 18, 19 48

Plugging completed May 24, 19 48

Reason for abandonment of well or producing formation Quit producing oil

If a producing well is abandoned, date of last production May 11, ~~1948~~ 19 48

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well C. D. Stough, Great Bend, Kansas.

Producing formation Viola Depth to top 3768' Bottom 3789' Total Depth of Well 3789' Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS — CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				8 5/8" OD	305'	None
				4½" OD	3767'	3095'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from ..... feet to ..... feet for each plug set.

Filled hole with chat from 3789' TD to 3760' and set cement plug using 4 sacks of cement from 3760' to 3748' then filled hole with heavy mud from 3748' to 300' and set cment plug from 300' to 255' using 15 sacks of cement then filled hole with heavy mud from 255' to 30' and set cement plug in top from 30' to bottom of cellar using 10 sacks of cement.

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to Champlin Refining Company

Address P. O. Drawer #552, Enid, Oklahoma.

6-1-48

STATE OF Kansas, COUNTY OF Barton, ss.

S. P. Hall (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) S P Hall

P. O. Box 167, Ellinwood, Kansas.
(Address)

SUBSCRIBED AND SWORN TO before me this 28th day of May, 19 48

N. Kenneth Stevens
Notary Public.

My commission expires October 24, 1951

22-2625 2-48—15M

PLUGGING
FILE SEC. 9 T. 24 R. 11 W
BOOK PAGE 31 LINE 40

15-185-12535-0000

CHAMPLIN REFINING COMPANY

FIGGER #4 WELL
CENTER SW¼ NE¼ NE¼
Stafford County, Kansas

FORMATION LOG

0 - 125' Sand & gravel
125' - 305' Shells & red bed
305' - 840' Red bed & shells
840' - 1215' Red Bed & Shale & Shells
1215' - 1420' Red Bed & Shale
1420' - 1520' Shale & Shells
1520' - 1675' Shale & Lime
1675' - 1765' Lime & Shale
1765' - 1910' Shale & Lime
1910' - 2065' Broken Lime & Shale
2065' - 2190' Lime & Shale
2190' - 2360' Shale & Lime
2360' - 2515' Lime & Shale
2515' - 2605' Shale
2605' - 2745' Shale & Lime Shells
2745' - 2895' Shale & Lime
2895' - 2975' Lime
2975' - 3060' Lime
3060' - 3120' Lime
3120' - 3205' Lime
3205' - 3250' Lime
3250' - 3280' Shale
3280' - 3310' Sand & Shale
3310' - 3385' Shale
3385' - 3445' Lime
3445' - 3500' Lime
3500' - 3560' Lime
3560' - 3610' Lime
3610' - 3665' Lime
3665' - 3725' Lime
3725' - 3770' Shale & Lime
3770' - 3775' Lime
3775' - 3781' Lime
3781' - 3789' Lime
3789' - Total Depth

MAY 28 1948

PLUGGING
FILE SEC 9 T 24 R 11W
BOOK PAGE 31 LINE 40