To:	$\begin{array}{c} 1_{020843} & 2 - 2.3 \\ 2_{020843} & 3_{0208433} & 3_{020843} & 3_{0208433} & 3_{0208433} & 3_{0208433} & 3_{0208433} & $	API NUMBER 15-185-22,989-0000				
CONSERVATI	PORATION COMMISSION ION DIVISION - PLUGGING SECTION ADO DERBY BUILDING	C NE NW . SEC.				
	KANSAS 67202	660	fee;t	from NS	section	line
	N'S PLUGGING REPORT			from W&		
	License / 30080	Lease Name McComb		Well	<u>3</u>	
Operator:	Honey Oil Company, Inc.	County Stafford			· ·	
	401 E. Douglas, Ste. 505	Well Total Depth	h	3826	124.35	_fee†
	Wichita, KS 67202	Conductor Pipe:				1/
	·	Surface Casing:				
Abandoned	Oll Well Gas Well 1	Input Well	_ SWD 1	Well	D&A	Х
Other well	1 as hereinafter indicated	· ·				
Plugging (Contractor Duke Drilling Company			se Number	5929	
Address3	310 W. Central, Wichita, KS 67202		-		•	
Comp any tr	o plug at: Hour: 1 p.m. Day:	23 Month:	2	Yea	r:19 95	-
	proposal received from R. Moore					
	Dula Dudiliana Company Inc			(phone)	316-267-1	331
•	fill hole with heavy mud and spot co					
	at 1275 with 50 sx cement, 2nd plu		. • •			
	at 40' with 10 sx cement,		-			
4th plug	to circulate rathole with 15 sx cemer	ent,				
	to circulate mousehole with 10 sx cen					
	Plugging Proposa			Glenn Bar		·
		I Received Dy		(TECHNIC)		
Plugg ing (Operations attended by Agent?: All_	Part_		None_	·X	
	s Completed: Hour: 3 p.m. Day:		2	Year	r:19 ⁹⁵	
	UGGING REPORT 1st plug at 1275' with	th 50 sx cement,			STATE CORPOR	CEIVED
2nd plug a	at 256' with 50 sx cement,					· · · · · · · · · · · · · · · · · · ·
3rd plug ;	at 40' with 10 sx cement,	,	· .		LLL	Z 7 199.
4th plug t	to circulate rathole with 15 sx cemen	ent,			CONSTRAIN	HON DIVI
5th plug	to circulate mousehole with 10 sx cer	ement.				* 12 mg = 1 mg =
Remarks:	Used 60/40 Pozmix 6% gel by United.	·				
4	(if additional description is ne	acessary, use BACK	K of th	his form.)	
I Maka O	did not) observe this plugging.	K.	1	11/	11)	\$
7-		Signed Ale	W (TECHN	NICIANS)	Mow	
The management		/				

FORM CP-2/3 Rev.01-84