STATE OF KANSAS Well Plugging Record API NUMBER 15-095-217490000 STATE CORPORATION COMMISSION K.A.R. -82-3-117 LEASE NAME Alameda 130 S. Markèt, Room 2078 WELL NUMBER 1-2 TYPE OR PRINT Wichita, Kansas 67202 NOTICE: Fill out completely and return 3760 Ft. from South Line of Section to Cons. Div. office within 30 days. 330 Ft. from East Line of Section LEASE OPERATOR KC Resources, Inc. SPOT LOCATION 130' N of Ne Se Ne **ADDRESS** P.O. Box 1118 Section 22 Townshp 28s CITY, STATE, ZIP Cardiff, California 92007 County Kingman PHONE# 760-753-3330 Date Well Completed Nov. 2, 1998 Dry and Abandoned Character of Well Date Plugging Commenced Nov. 2, 1998 (Oil, Gas, D&A, SWD, Input, Water Supply Well) Date Plugging Completed Nov. 2, 1998 The plugging proposal was approved on October 29, 1998 at 9:30 am (date) **Butch Hollbrite** by (KCC District Agent's Name Is ACO-1 Filed? If not, is well log attached? Yes D&A Producing Formation(s) Depth to Top **Bottom** T.D. 4085 Show depth and thickness of all water, oil and gas formations. OIL, GAS OR WATER RECORDS CASING RECORD **FORMATION** CONTENT FROM lto. SIZE **PUT IN** PULL OUT Surface Soil and Sands Water sands and Clays 0 30 and Redbeds 30 Shale 215 8-5/8" 196,981 0' Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, feet each set. Plugged well as follows using 60/40 Poz, 4% Gel: Filled hole with heavy mud from 4085' to 1175'. Then 35 sacks cement. Heavy mud from 1175' to 725'. Then 35 sacks cement. Heavy mud to 260' then 35 sacks cement. Heavy mud to 60' then 25 sacks of cement. Plugged rathole with 15 sacks and the mousehole with 10 sacks. Started plugging well at midnight 11-02-98 and plug down at 2:00 am on 11-02-98. Name of Plugging Contractor Sterling Drilling Company Licence No. 5142 Address P.O. Box 1006 City: Pratt State: Kansas Zip 67124 NAME OF PARTY RESPONSIBLE FOR PLUGGING FEES: KC Resources, Inc. (Operator STATE OF **COUNTY OF** PRATT ,ss. Steve E. McClain, Agent (Employee of Operator or (Operator) of above described well, being firs duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above described well as filed that the same are true and correct, so help me God. (Signature) (Steve E. McClain, President of Sterling Drilling Company)

SUBSCRIBED AND SWORN TO me this 104h day of November 1, 19 98

NOTARY PUBLIC - State of Kansas My Appt, Exp. 2

P.O. Box 1006

Damole S. Frelds

Form CP-4 Revised 12-92

Zip 67124

State: Kansas

(Address)

15-095-21749-0000

Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006 Office Phone (316) 672-9508, Fax 672-9509

SAMPLE LOG

Alameda 1-2

LOCATION:

130' N of Ne Se Ne

Section 22

22 T 28s

R 7w

API:

15-095-217490000

Kingman County, Kansas

OWNER: KC Resources, Inc./RMS Energy, Inc.

COMMENCED:

27-Oct-98

CONTRACTOR: Sterling Drilling Company, Rig #4

COMPLETED:

02-Nov-98

TOTAL DEPTH:

DRILLER

4085 FEET

Ground Elevation:

1581

LOGGER

4086 FEET

KB Elevation:

1591

LOG

29 FEET

Top Soil and Sand

29 -

0 -

1000 FEET

Redbeds/Shales

1000 -

4085 FEET

Shale/Limestone and Chert.

CASING RECORDS

Spud @ 7:30 am on 10-27-98. Drilled 12-1/4" hole to 215'. Ran 5 joints of used 20# 8-5/8" surface casing 196.98' set at 210' KB. Cemented with 170 sacks 60/40 Poz, 2% Gel, 3% CC. Plug down at 1:15 pm on 10-27-98 by Halliburton. Good returns. Ticket # 459990.

Received plugging orders at 9:30 am on 10-29-98 from Butch Hollbrite.

Plugged well as follows using 60/40 Poz, 4% Gel:

Filled hole with heavy mud from 4085' to 1175'. Then 35 sacks cement.

Heavy mud from 1175' to 725'. Then 35 sacks cement.

Heavy mud from 725' to 260. Then 35 sacks cement.

Heavy mud from 260' to 60'. Then 25 sacks cement.

Plugged rathole with 15 sacks and the mousehole with 10 sacks.

Started plugging well at midnight 11-02-98 and plug down at 2:00 am on 11-02-98.

INDEAS CORP COLL.

DEVIATION SURVEYS

1/2 degree(s) at 215 feet 1 degree(s) at 4012 feet