

1 060548

R

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION SW SW NE , SEC. 13 , T 24 S, R 18 W/NE
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 047-21,250-0000

2970 feet from S section line
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5056

Lease Name D. McKinney Well # "B" 1-13

Operator: F. G. Holl

County Edwards 149.34

Name & Address 6427 East Kellogg

Well Total Depth 4595 feet

Wichita, KS 67207

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 300

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Sterling Drilling Co. License Number 5142

Address Box 129, Sterling, KS 67579

Company to plug at: Hour: 8:00 pm Day: 21 Month: April Year: 19 85

Plugging proposal received from Jim Shriner

(company name) Sterling (phone) 316-278-2131

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 1190' with 50 sx cement

2nd plug at 600' with 50 sx cement

3rd plug at 320' with 50 sx cement

solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Paul A. Luthi

(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 10:30 pm Day: 21 Month: April Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 1190' with 50 sx cement, 2nd plug at 600' with 50

sx cement, 3rd plug at 320' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with

15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

APR 23 1985

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburton.

(If additional description is necessary, use BACK of this form.)

(check and sign) observe this plugging.

Signed Paul A. Luthi
(TECHNICIAN)

DATE 5-3-85

INV. NO. 7923