SIDE ONE

Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansas days after the completion of a well, regardless of he Attach separate letter of request if the information on record and Side Two will then be held confidential. Applications must be made on dual completion, coinjection and temporarily abandoned wells. Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC	s 67202, within thirty (30) by the well was completed. ation is to be held confidential. Side One will be of public bommingling, salt water disposal, ical log, sonic log, gamma ray						
ICENSE # 5313 EXPIRATION DATE June 30, 1983 PERATOR F & M OIL CO., INC. API NO.15-047-21,064-0000							
	COUNTY Edwards						
Wichita, Kansas 67202							
** CONTACT PERSON E. A. Falkowski PHONE (316)262-2636	•						
PURCHASER	LEASE Britton						
• • • • • • • • • • • • • • • • • • • •	WELL NO. 1						
	WELL LOCATION NW SE SW						
•	990 Ft. from South Line and						
CONTRACTOR	1650 Ft. from West Line of						
ADDRESS 422 Onion Center	the SW (Qtr.)SEC 3 TWP24S RGE 18W.						
Wichita, Kansas 67202 PLUGGING Union Drilling Co., Inc.	WELL PLAT (Office						
CONTRACTOR	Use Only)						
ADDRESS 422 Union Center	KCC						
Wichita, Kansas 67202	KGS						
TOTAL DEPTH 4620' PBTD	SWD/REP PLG.						
SPUD DATE DATE COMPLETED	3						
ELEV: GR 2161' DF 2164' KB 2166'							
DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS. DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE							
Amount of surface pipe set and cemented 458'w/300	OV Tool Used? None .						
THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas, S Injection, Temporarily Abandoned, OWWO. Other							
ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATION AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	ONS PROMULGATED TO REGULATE THE OIL						
<u>A F F I D A V I T</u>							
that:	ing of lawful age, hereby certifies						
I am the Affiant, and I am familiar with the con The statements and allegations contained therein are	true and correct.						
	(Name)						
SUBSCRIBED AND SWORN TO BEFORE ME this 8th	(
19_82.							
	Shirley Ch. Dalless						
MY COMMISSION EXPIRES: 12-24-84	Shirley A. Gallegos						
MY COMMISSION EXPIRES: 12-24-84 ** The person who can be reached by company megarding a sufformation. SEP 1 0 1982	any questions concernions, this						
SEP 1 0 1982	CONCES.						
0 1002	CONSERVATION DIVISION WICHITA. Kansas						
CONSERVATION DIVISION Wichita, Kansas	Nansas						

LEASE Britton #1 SEC. 3 TWP. 245 RGE. 18W

	FILL IN	SHOW GEO	SHOW GEOLOGICAL MARKERS, LOGS RUN,						
Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, in- cluding depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.						OR OTHER DESCRIPTIVE INFORMATION.			
FORMATION DESCRIPTION, CONTENTS, ETC.			ТОР	воттом	NA	ME	DEPTH		
DST#1 4111-4125', Lansing J Zone 30-30-30-30, wk blow died in 17", no blow on 2nd open, rec 30' mud, no IFP or ISIP tool plugged, FFP 50-110#, FSIF 1342#, slight plugging action on 2nd open.			,		Sample Anhydr B/Anhy Heebne Toront Dougla Br/Lin	ydrite er o as Sh	1214(+ 952 1231(+ 935 3799(~1633 3816(-1650 3828(-1662 3911(-1745		
DST#2 4415-4450', Cherokee Sand 30-45-60-45, blow off btm of bucketcin 1", GTS in 75", gas gauged in 15" 15.2 MCF, 30" 18.8 MCF, 60" 22.4 MCF on ½" orfice, rec 180' GCM, 360' GCMW w/few spks, IFP 243-232#, ISIP 1375#, FFP 210-210#, FSIP 1429#.						ee Sh			
DST#3 4471-4482', Mississippi 30-30-30-30, wk blow thruout 1st open, no blow on 2nd open, rec 50' mud, plug- ged tool on 1st open, slight plugging on 2nd open, IFP & ISIP none, FFP 65- 188#, FSIP 1320#.		,		Electric I Anhydrite B/Anhydrit Heebner Toronto Douglas SI Br/Lime Lansing B/KC		Tops: 1215 (+ 951 1233 (+ 933 3797 (-1631 3812 (-1646 3825 (-1659 3910 (-1744 3918 (-1752 4226 (-2060			
						1	ee Sd		
Report of all string	s set — surface, i	intermediate,	production, etc	. CASING	RECORD (N	ew) or (I	Jsed)		
Purpose of string	Size hole drilled	Size casing set	Weight lbs/ft.	Setting depth	Type cement	Sacks T		pe and percent additives	
Surface	121/4."	8-5/8"	24#	458'	common	300	2%	2% gel, 3% CC	
LINER RECORD				PERFORATION RECORD					
Top, ft.	Bottom, ft.	Sacks o	ement	Shots	per ft.	Sixe & type	ype Depth interval		
:	TUBING RECO	ORD		İ					
Size Setting dopth Packer set at:									
		ACID, FRACT	TURE, SHOT,	CEMENT SQ	UEEZE RECORD		.		
Amount and kind of material used Depth interval treated								rval treated	
				.					
Date of first production Producing mothod (flowing, pumping, gas lift, atc.)						Gr	Gravity No.		
RATE OF PRODUCTION PER 24 HOURS	Oil	_	Gas bls.		MCF Water %		Gos-oli.voi	tio	
Disposition of gos (vented, used on lease or sold)									