

To: 1 090204  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

7-16 API NUMBER 15-185-22,856-0000 198R

SW NE SE, SEC. 9, T. 24 S, R. 14 W EX  
1650 feet from S section line  
990 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5097  
Operator: Martin Oil Producers, Inc.  
Name & Address: 150 N. Main, Suite 1010  
Wichita, KS 67202

Lease Name Cotton Well # 1  
County Stafford  
Well Total Depth 4275 138.93 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 310

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allen Drilling Company License Number 5418  
Address P.O. Box 1389, Great Bend, KS 67530-1389

Company to plug at: Hour: \_\_\_\_\_ Day: 16 Month: 7 Year: 19 92

Plugging proposal received from Mike Kerns  
(company name) Allen Drilling Company (phone) 316-793-5681

was: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 906-927'  
1st plug at 930' with 50 sx cement,  
2nd plug at 330' with 50 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None x  
Operations Completed: Hour: 11:45 p.m Day: 16 Month: 7 Year: 19 92

ACTUAL PLUGGING REPORT 1st plug at 930' with 50 sx cement,  
2nd plug at 330' with 50 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
Water well plugged with 15 sx.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. RECEIVED  
(If additional description is necessary, use BACK of this form.) CORPORATION COMMISSION

INVOICED  
observe this plugging.

DATE 8-4-92  
INV. NO. 35854

Signed [Signature] IIII 29 1992  
(TECHNICIAN)