RECEIVED CP-3
RECEIVED CP-3
RECEIVED CP-3
STATE CORPORATION COMMISSION TATE CORPORATION DIVISION DI VISION DI DIVISION DI VISION DI VISION DIVISION DI VISION DI VISIONI DI VISION DI VISION DI VISION DI VISIONI DI VIS

CONSERVATION DIVISION AGENT'S REPORT

CONSERVATION DIVISION Wichita. Kansas

J. Lewis Brock Administrator P. O. Box 17027 Wichita, Kansas 67217

Complete Address 1300								
Lease Name Pipkin			~	We]	l No	<u>. </u>		
Location C SE/NE				Sec. 2	Twp. 2	8_Rge.	<u>5</u> (e)	(W
County Kingman					_Total	Depth	3903	<u> </u>
Abandoned Oil Well X	Gas Well	·	Input	We11	SWI	D Well		& A
Other well as hereafter	indicated_					 _		
Plugging ContractorV	oth Casin	g Pulli	.ng					
Address 715 S. Ave	Arkansas	City, K	S		Lice:	nse No.	684	
Operation Completed:								1975
220 ft 8 5/8 surface	e cemente	d with						
220 ft 8 5/8 surface	ce cemente	d with	3799	ft.	Sand t	o 3780	ft,	5 sac
220 ft 8 5/8 surfac	ce cemente	d with	3799	ft.	Sand t	o 3780	ft,	5 sac
220 ft 8 5/8 surface	ce cemente koks. Top . Pulled	od with perf.	3799 t 5音。	ft. Set	Sand t	o 3780	ft,	5 sac
cemented with 60 second with bailer	ce cemente koks. Top . Pulled	od with perf.	3799 t 5音。	ft. Set	Sand t	o 3780	ft,	5 sac
cemented with 60 second with bailer	ce cemente koks. Top . Pulled	od with perf.	3799 t 5音。	ft. Set	Sand t	o 3780	ft,	5 sac
cemented with 60 second with bailer	ce cemente koks. Top . Pulled	od with perf.	3799 t 5音。	ft. Set	Sand t	o 3780	ft,	5 sac
cemented with 60 second with bailer	ce cemente koks. Top . Pulled	od with perf.	3799 t 5音。	ft. Set	Sand t	o 3780	ft,	5 sac
220 ft 8 5/8 surface cemented with 60 second with bailer 290 ft. Fill hole	ce cemente Roks. Top Pulled with 5 ye	od with perf. 3000 f	3799 t 5½. nix to	ft. Set	Sand t	nock t	ft,	5 sac
cemented with 60 seconds with bailer	ce cemente Roks. Top Pulled with 5 ye	od with perf. 3000 f	3799 t 5½. nix to	ft. Set	Sand t	nock t	ft,	5 sac