

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

OR

FORMATION PLUGGING RECORD

Strike out upper line
when reporting plug-
ging off formations.

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bittling Building
Wichita, Kansas

Reno County. Sec. 34 Twp. 23S Rge. 4W (E) (W)

Location as "NE 1/4 NW 1/4 SW 1/4" or footage from lines. SE SW NE

Lease Owner. Barnsdall Oil Company

Lease Name. H. Baughman Well No. 2

Office Address. Box 2039, Tulsa, Okla.

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date, well completed. Apr. 20th, 1935 19

Application for plugging filed. March 18th, 1941 19

Application for plugging approved. 19

Plugging Commenced. March 23rd, 1941 19

Plugging Completed. March 31st, 1941 19

Reason for abandonment of well or producing formation.

Not producing in paying quantities

If a producing well is abandoned, date of last production. March 17th, 1941 19

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well. ~~Harriet E. Baker~~ E. T. Alexander

Producing formation. Chat Depth to top. 3246 Bottom. 3380 Total Depth of Well. 3516' Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD


Formation	Content	From	To	Size	Put In	Pulled Out
Chat	Oil & Gas	3246	3380'	16"	200.13'	None
				13"	643.20'	186' 2"
				7"	3600.23'	2873' 5"

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from.....feet tofeet for each plug set.

Filled from 3516' to 3270' with Mud. Set 6 sack cement plug from 3270' to 3255'.
Filled with mud from 3255 to 2800'. Pulled 7" Casing. Filled with mud to bottom of
13". Pulled 13" Casing and filled with mud to 190'. Bridged solid at 190' with
rock. Run 20 Sacks cement from 190 to 170'. Filled with mud from 170' to 14'.
Filled with 10 sacks cement from 14' to cellar base.

4-19-41

PLUGGING
FILE 34 23R 4W
BOOK PAGE 131 LINE 33



(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to. The Barnsdall Oil Co
Address. Box 2039, Tulsa, Okla.

STATE OF....., COUNTY OF....., ss.
..... (employee of owner) or (owner or operator) of the above-described well,
being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-
described well as filed and that the same are true and correct. So help me God.

(Signature) *H. Baughman*

(Address)

SUBSCRIBED AND SWORN TO before me this 7th day of April, 1941

Harriet E. Baker
Notary Public.

My commission expires 7-22-43

15-155-02697-0000

H. Baughman Well No. 2
 330' North and 330' West of SE Corner of Lease, W2,
 NE/5 Section 34-23S-4W, Reno Co., Kansas

Drilling Commenced: 2-21-35
 " completed: 4-20-35
 Drilled by: Noble Drilling Co.

CASING RECORD:

16"OD 55# 8thd Nat' 10 jts. 200.13' Set @ 205.33' w/350 Sacs Cement
 13"OD 50# LW 32 joints 643.20' Set @ 643.75' w/175 Sacs Cement
 7"OD 22# 10thd SS 153 joints 3600.23' Set @ 3606.00' w/ 375 Sacs Cement

INITIAL PRODUCTION: 303 bbls /24hours pumping potential (4-23-35)

FORMATION RECORD:

Sand	0	135	Note: Plugged Back from 3690' to 3516' w/chat and cement
Shale & Shells	135	206	
Shale	206	360	
Salt & Lime	360	499	
Shale	499	505	
Lime & Salt, broken	505	508	
Anhydrite & Salt	508	528	
Anhydrite & Lime	528	575	
Lime & Shale	575	602	
Shale	602	645	
Lime	645	780	
Lime & Shale, Broken	780	930	
Red Bed	930	940	
Lime, Broken	940	1065	
Shale & Lime	1065	1400	
Shale & Shells	1400	1680	
Shale & Lime	1680	1990	
Lime	1990	2025	
Shale & Shells	2025	2093	
Lime, Shale Broken	2093	2152	
Lime, Broken	2152	2280	
Shale & Shells	2280	2316	
Lime & Shale, Broken	2316	2379	
Shale, Blue	2379	2437	
Sand	2437	2485	
Shale, Broken	2485	2560	
Lime 2560	2560	2942	
Shale	2942	3246	
Chat	3246	3379	
Chat & Lime	3379	3401	
Lime	3401	3435	
Lime, Hard	3435	3454	
Lime	3454	3482	
Shale & Lime	3482	3501	
Sand	3501	3507	
Shale and Lime	3507	3585	
Shale	3585	3606	
Lime 3606	3606	3678	
Shale	3678	3685	
Shale and Lime	3685	3688	
Lime	3688	3690	Total Depth

PLUGGING
 FILE 34-23S-4W
 BOOK SE 137 LINE 33

MAR 27 1935
 STATE OF KANSAS
 COUNTY OF RENO