

1 060240

8-8

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 083-21,411-0000

C NW NE, SEC. 1, T 24 S, R 22  
660 feet from NW section line  
1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License / 31425  
Operator: Princess Three Corporation  
Name & Address: P.O. Box 1983  
Henderson, TX 75653-1983

Lease Name Hall Well / 1  
County Hodgeman 152.75  
Well Total Depth 4700 feet  
Conductor Pipe: Size 8 5/8 feet 287  
Surface Casing: Size feet

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Emphasis Drilling Company License Number 8241

Address P.O. Box 819, Russell, KS 67665-0819

Company to plug at: Hour: 8 p.m. Day: 8 Month: 8 Year: 1994

Plugging proposal received from Bill Owen

(company name) Emphasis (phone) 913-483-3518

Remarks: to fill hole with heavy mud and spot cement through drill pipe  
1st plug at 1450' with 50 sx cement, 2nd plug at 650' with 50 sx cement,  
3rd plug at 320' with 50 sx cement, 4th plug at 40' with 10 sx cement,  
5th plug to circulate rathole with 15 sx cement,  
6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Case Morris (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 11:30 p.m. Day: 8 Month: 8 Year: 1994

ACTUAL PLUGGING REPORT 1st plug at 1450' with 50 sx cement,

2nd plug at 650' with 50 sx cement,

3rd plug at 320' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

INVOICED

(XXX / did not) observe this plugging.

DATE 9-6-94

INV. NO. 41114

Signed [Signature] (TECHNICIAN)

RECEIVED  
STATE CORPORATION COMMISSION

AUG 11 1994

CONSERVATION DIVISION  
WICHITA, KANSAS