

To: 1090510 12-10  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-083-21,420-0000  
S/2 NE, SEC. 4, T 24 S, R 22 W/E  
1980 feet from N & section line  
1320 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 3988  
Operator: Slawson Exploration Company, Inc.  
Name & Address 621 N. Robinson, Ste. 490  
Oklahoma City, OK 73102

Lease Name Stoecker Z Well # 1  
County Hodgeman  
Well Total Depth 4770 155.03 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 620

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SMD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor L.D. Drilling, Inc. License Number 6039

Address RR 1, Box 183 B, Great Bend, KS 67530

Company to plug at: Hour: 7:30 a.m. Day: 10 Month: 12 Year: 19 94

Plugging proposal received from Greg Davison

(company name) L.D. Drilling, Inc. (phone) 316-793-3051

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1475'

1st plug at 1480' with 50. sx cement, 2nd plug at 650' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Middleton  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 9 a.m. Day: 10 Month: 12 Year: 19 94

ACTUAL PLUGGING REPORT 1st plug at 1480' with 50 sx cement,

2nd plug at 650' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

DEC 14 1994

CONSERVATION DIVISION  
WICHITA, KANSAS

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

I (did not) observe this plugging.

Signed [Signature]  
(TECHNICIAN)

DATE 1-5-95

INV. NO. 41980

12-10