STATE CORPORATION COMMISSION ive All Information Completely						Form CP-
ake Required Affidavit all or Deliver Report to:  Conservation Division		WE	LL PLU	GGING RI	ECORD	W
State Corporation Commission		Hodge	nan Count	s.a. 4 т	24 <b>p</b> _22	(E)(W
Wichita, Kansas 67202	Location as "N	JE/CNWESWE" o	r footage fro	m lines NE	NE '	(¥,
NORTH 155 S	The Lease Owner	Thund	erbird D	rilling, I	nc.	
The state of the s	Y cose Nome	Stock	er #1			Well No
	1	Wichi			<del></del>	
	1	Well (completed a	-	•		
}		npleted				
	Application for	r plugging filed				
i l i	Plugging com	r plugging nied r plugging approvemenced	3/24/70			19
!!!	Plugging com		3/27/70			19
	Reason for aba	andonment of well	or producing	g formation	depleted.	
i l		<del></del>		-	<del></del>	
		well is abandone		_		
Locate well correctly on above	_			ation Division o	r its agents befor	re plugging was con
Section Plat ame of Conservation Agent who supe		yes his well			<del>-</del>	
oducing formation		Depth to top	Botton		Total Depth of V	Vell 4608 Fee
low depth and thickness of all water,						
OIL, CAS OR WATER RECORD						ASING RECORD
		<del></del>			1	
FORMATION	. CONTENT	FROM	TO	SIZE	PUT IN	PULLED DUT
				8-5/8	450	none
				<u> </u>	4591 '	2455!
				1	1 1	
Describe in detail the manner in introducing it into the hole. If cem feet for each plug se	ent or other plugs v		_			
checked hole cement. Sho	to 4150', rate pipe at 366, 2450', got	n sand to 4 2', 2577', loose and p	080' and	f same and dept	ks of	
cement. Sho	to 4150', ra	n sand to 4 2', 2577', loose and p	080' and	f same and dept	ks of	
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 0021, 2878 joints.	h placed, from ks of ', 2730', Pumped	feet
cement. Sho	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 0021, 2878 joints.	h placed, from ks of ', 2730', Pumped	feet
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 0021, 2878 joints.	h placed, from ks of ', 2730', Pumped	feet
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  cement. Sho 2603', 2576'  lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	D
checked hole  cement. Sho 2603', 2576'  lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet (
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole cement. Sho 2603', 2576' lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  cement. Sho 2603', 2576'  lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  cement. Sho 2603', 2576'  lo sacks mud	to 4150', rate pipe at 366, 2450', got and 50 sacks	n sand to 4 2', 2577', loose and p	080' and	ran 5 sac 002', 2878 joints.	ks of ', 2730', Pumped  RECEIVE	D
checked hole  cement. Sho 2603', 2576'  lo sacks mud	to 4150', rat pipe at 366, 2450', got and 50 sacks	vere used, state the new sand to 4 2', 2577', loose and profession of cement.	280' and 3208', 3ulled 75	ran 5 sac color co	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  Checked hole  cement. Sho  2603', 2576'  10 sacks mud  PLUGGING COM  PLUGGING COM	to 4150', rate plugs were to 4150', rate pipe at 366, 2450', got and 50 sacks	vere used, state the man sand to 4 2', 2577', loose and post of cement.	280' and 3208', 3ulled 75	ran 5 sac color co	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  Checked hole  cement. Sho  2603', 2576'  10 sacks mud  PLUGGING COM  PLUGGING COM	to 4150', rate plugs were to 4150', rate pipe at 366, 2450', got and 50 sacks	vere used, state the new sand to 4 2', 2577', loose and profession of cement.	280' and 3208', 3ulled 75	ran 5 sac color co	ks of ', 2730', Pumped  RECEIVE	feet '
checked hole  Checked hole cement. Sho 2603', 2576' 10 sacks mud  PLUGGING COM  PLUGGING COM  ame of Plugging Contractor  ddress	to 4150', rate plugs were to 4150', rate pipe at 366, 2450', got and 50 sacks  PLETE.  (If addition KNIGHT CHASE,	vere used, state the many sand to 4 (2', 2577', 100se and profession of cement.	280' and 3208', 3ulled 75	ran 5 sac color co	ks of ', 2730', Pumped  RECEIVE	feet (
checked hole cement. Sho 2603', 2576' 10 sacks mud  PLUGGING COM  ame of Plugging Contractor ddress	to 4150', rat pipe at 366, 2450', got and 50 sacks  PLETE.  (If addition KNIGHT CHASE,	al description is neces CASING PULL KANSAS	080' and 3208', 3 ulled 75	ran 5 sac color control contro	RECEIVE SEP 2 2 1976 RVATION DIVI	D MMISSION SION
checked hole cement. Sho 2603', 2576' lO sacks mud  PLUGGING COM  PLUGGING COM  TATE OF	to 4150', ra t pipe at 366 , 2450', got and 50 sacks  PLETE.  (If addition KNIGHT CHASE,	al description is necessing PULL KANSAS	D80' and 3208', 3 alled 75	ran 5 sac color co	RECEIVE CORPORATION CON SEP 2 2 1970 Ichita, Kansas	D MMISSION SION
ame of Plugging Contractor  ddress  TATE OF  feet for each plug segment. Shown 2603', 2576'  10 sacks mud  PLUGGING COM	to 4150', ra t pipe at 366 , 2450', got and 50 sacks  PLETE.  (Haddition KNIGHT CHASE,  KANSAS NOEL J.  says: That I have k	vere used, state the many sand to 4 (2', 2577', 100se and proof cement.  CASING PULL KANSAS  OUNTY OF RIKNIGHT (emowledge of the formula in the state of the stat	D80' and 3208', 3 ulled 75	ran 5 sac cool 2878 joints.  STATE Coolse W.	RECEIVE CORPORATION CON SEP 2 2 1970 Ichita, Kansas	D MMISSION SION
checked hole cement. Showers mud  PLUGGING COM  PLUGGING C	to 4150', ra t pipe at 366 , 2450', got and 50 sacks  PLETE.  (Haddition KNIGHT CHASE,  KANSAS NOEL J.  says: That I have k	vere used, state the many sand to 4 (2', 2577', 100se and proof cement.  CASING PULL KANSAS  OUNTY OF RIKNIGHT (emowledge of the formula in the state of the stat	D80' and 3208', 3 ulled 75	ran 5 sac cool 2878 joints.  STATE Coolse W.	RECEIVE CORPORATION CON SEP 2 2 1970 Ichita, Kansas	D MMISSION SION
checked hole cement. Showers mud  PLUGGING COM  PLUGGING C	to 4150', ra t pipe at 366 , 2450', got and 50 sacks  PLETE.  (Haddition KNIGHT CHASE,  KANSAS NOEL J.  says: That I have k	vere used, state the many sand to 4 (2', 2577', 100se and proof cement.  CASING PULL KANSAS  OUNTY OF RIKNIGHT (emowledge of the formula in the state of the stat	D80' and 3208', 3 ulled 75	ran 5 sac cool 2878 joints.  STATE Coolse W.	RECEIVE CORPORATION CON SEP 2 2 1970 Ichita, Kansas	D MMISSION SION
checked hole  Checked hole  cement. Sho  2603', 2576'  10 sacks mud  PLUGGING COM  PLUGGING COM  Ame of Plugging Contractor  ddress	to 4150', ra t pipe at 366 , 2450', got and 50 sacks  PLETE.  (Haddition KNIGHT CHASE,  KANSAS NOEL J.  says: That I have k	al description is necessing PULL KANSAS  OUNTY OF RIKNIGHT (emowledge of the imand correct. So here	D80' and 3208', 3 ulled 75	converse owner) or (owners, and matter	RECEIVE CORPORATION CON SEP 2 2 1970 Ichita, Kansas	D MMISSION SION

August

nargaset Melcher Notary Public.