



McElwain No. 2

15-155-30209-0000

Top	Bottom	Formation and Remarks
0	145	Sand
145	155	Shale set 15 1/2" Cemented
155	291	Shale & Shells
291	460	Shale & Shells
460	475	Lime Shells
475	500	Shale & Shells 12 1/2" Casg.
500	581	Lime Shells
581	718	Lime & Shale Breaks
718	920	Shale & Shells
920	1045	Shells & Lime Shells
1045	1230	Shale & Shells
1230	1594	Shale-Acid Test 1500
1594	1657	Shale & Lime
1657	1839	Shale
1839	1978	Shale & Lime
1978	2064	Shale & Shells
2064	2138	Lime & Shale
2138	2274	Shale
2274	2319	Shale & Lime
2319	2389	Lime
2389	2440	Lime & Sand
2440	2449	Lime
2449	2523	Shale & Shells
2523	2533	Sand & Lime
2533	2896	Lime
2896	2908	Broken Lime
2908	2915	Lime
2915	2977	Shale
2977	3018	Broken Lime & Shale
3018	3023	Lime & Shale
3023	3054	Lime
3054	3063	Lime & Shale
3063	3084	Hard Lime
3084	3091	Lime & Shale
3091	3119	Shell & Lime
3119	3146	Shale
3146	3189	Shale & Lime Shells
3189	3224	Shale-Lime Shells
3224	3247	Shale
3247	3328	Chat
3328	3369	Broken Lime & Chat
3369	3395	Broken Lime Shale
3395	3466	Lime
3466	3475	Shale & Lime Shells
3475	3480	Sand & Lime

Casing Record

15 1/2" - 167' 8"  
 12 1/2" - 567' 1"  
 8 5/8" - 3581' 6"

3480	3494	Broken Lime & Shale
3494	3502	Shale
3502	3522	Broken Lime Shale
3522	3565	Shale
3565	3582	Cored
3582	3588	Lime Core Layed down 6"
		Drill pipe, started
		running 8 1/4". Run and
		cemented 3581' 8 1/4" Csg.
3582	3593	Hunton Lime. Total Depth

SEP 9 X 1950  
 STATE CORPORATION  
 COMMISSION  
 CIVIL  
 vation-Div.

AUG 9 - 1950  
 CORPORATION  
 COMMISSION  
 KANSAS

**PLUGGING**  
 FILE SEC. 347-23  
 BOOK PAGE 20-LINE 21