State of Kansas NOTICE OF INTENTION TO DRILL

FORM MUST BE SIGNED ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

ו האבוומבו	ME NE ME - 5 · 30 · 5 · East
Expected Spud Date January 1, 1989	NE NE Sec 5 Twp ³⁰ S, Rg ⁵ XX West
month day year	4050
⊏1 7.1	
OPERATOR: License #5171	330 feet from East line of Section
Name: TXO Corporation Address: 1660 Lincoln St. #1800	(Mote: Locate well on Section Plat Below)
Address: 1000 LiftCotti Sc. #1000	Thomas
City/State/Zip: Denver, CO. 80264	County: Kingman
Contact Person: Korrie West	Lease Name: .Sheetz Well #:1
Phone: (303) 861-4246	Field Name:
	Is this a Prorated Field? yes 🗶 .no
CONTRACTOR: License #:5418	
Name: Allen Drilling Company	Target Formation(s):
	Ground Surface Elevation:1506 feet MSL
Well Drilled For: Well Class: Type Equipment:	Domestic well within 330 feet: yes .X. no
	Municipal well within one mile: yes .X. no
Oil Inj Infield .X Mud Rotary	Depth to bottom of fresh water: .50
X Gas Storage .X Pool Ext Air Rotary	Depth to bottom of usable water: 100 /80
.X OWWO Disposal Wildcat Cable	Surface Pipe by Alternate: 1 .X. 2
Seismic; # of Holes	Length of Surface Pipe Planned to be set: Already set @130
the decourage for the contract of	Length of Conductor pipe required: N/A
If OMANO: old well information as follows:	Projected Total Depth: .3450
Operator: E.F. Wakefield	Formation at Total Depth: Staulnaker
Well Name: Esther Snyder #1	
Comp. Date: 1/8/54 Old Total Depth 4750	Water Source for Drilling Operations:
Comp. Date: +/3/33 Old folal Depth	well farm pond other
at at the object of the first and the second of the second	DWR Permit #:
Directional, Deviated or Horizontal wellbore? yesX. no	Will Cores Be Taken?: yes no
If yes, total depth location:	If yes, proposed zone:
AFFIDAVIT	ecosivid
The undersigned hereby affirms that the drilling, completion and eve	entual plugging of this wall of Form This R. C. W. C. W.
et. seq.	antidat progging of this water with company managers possessing
It is agreed that the following minimum requirements will be met:	VW () - 11 - 87
1. The appropriate district office shall be notified before se	etting surface pipe;
2. The minimum amount of surface pipe as specified above shall be set through all uncorrection materials plus	be set by circulating cement to the top; in all cases surface
pipe shall be set through all unconsolidated materials plus 3. If the well is dry, a plugging proposal shall be submitted	s a minimum of 20 feet into the UnderLyungUngungtony
and the district office on plug length and placement is nec	cessary prior to plugging;
 The appropriate district office will be notified before well 	ll is either plugged or production casing is cemented in:
If an Alternate II completion, production pipe shall be ceme	ented from below any usable water to surface within 120 days
of spud date. In all cases, notify district office prior?	to any cementing.
I hereby certify that the statements made herein are true and to the	
Date: Jan. 10, 1989. Signature of Operator or Agents	Title Agent
·	
-	
5280	R KCC USE:
5280	
4950 4620 API	1 # 15- 095-01,011 000 TOA
4950 4620 API	1 # 15- 095-01,011 050 A Inductor pipe required feet The part of the
4950 4950 4620 4629 3960 Min 3630	nductor pipe required feet per Alt. X 2 who proved by: LLM 1-13-89
4950 4620 4620 4290 3960 Min 3630 App	rective Date: 1-18-89
4950 4950 4620 4290 3960 33300 EFF 2970	t # 15- 095-01,011 000 feet per Alt. X2 consider the control of th
4950 4950 4620 4290 3960 3630 3300 EFF 2970 Thi	r # 15- 095-01,011 050 feet Inductor pipe required feet I
4950 4950 4290 3960 3630 3300 42970 2970 2970 2640 2310 6	nductor pipe required feet proved by:
4950 4950 4620 4290 3960 3960 3630 33300 2970 2970 2970 2970 2010 1980 1650	r # 15- 095-01,011 050 feet Inductor pipe required feet I
4950 4950 4620 4290 3960 3960 33300 2970 2970 2970 2640 2970 2070 1980 1650 1320	nductor pipe required feet proved by:
4950 4950 4290 3960 3960 3300 2970 2970 2640 1980 1980 1980 1990	nductor pipe required feet nimum surface pipe required /30 feet per Alt. X2 proved by:
4950 4620 4290 3960 3960 33300 2970 2970 2640 22310 1980 1650 1320 990 660 3300 - File Drill Pit A	nductor pipe required feet inform surface pipe required /30 feet per Alt. X2 proved by:
4950 4950 4620 4290 3960 3960 3300 2970 2970 2970 2640 2310 1980 1650 1320 990 660 330 - File Drill Pit A - File Completion	nductor pipe required feet inductor pipe required feet proved by:
4950 4950 4950 4950 4950 4950 3960 3960 3630 3300 EFF Thi 2640 2970 2970 2970 1980 1650 1320 990 660 330 - File Drill Pit A - File Completion - File acreage att	nductor pipe required feet inform surface pipe required /30 feet per Alt. X2 proved by:

- Obtain written approval before disposing or injecting salt water.

State of Kansas



MIKE HAYDEN KETTH R. HENLEY RICH KOWALEWSKI MARGALEE WRIGHT JUDITH McCONNELL FRANK A. CARO, JR.

GOVERNOR CHAIRMAN COMMISSIONER COMMISSIONER EXECUTIVE DIRECTOR GENERAL COUNSEL

Kansas Corporation Commission

CONSERVATION DIVISION SHARI M. FEIST, DIRECTOR 200 Colorado Derby Bldg. 202 W. 1st Street Wichita, KS 67202-1286 (316) 263-3238

MEMORANDUM

TO:

Shari Feist Albrecht

FROM:

Kris Moore

DATE: January 13, 1989

RE:

Table 1 exception for TXO Production Corp.,

Kingman County, Sec. 5-T30S-R5W, Sheetz #1 OWWO.

The above mentioned operator is seeking an exception to the Table 1 (one) rule for surface pipe in Kingman County, Kansas. The well to be washed down presently has 130' of 8 5/8" casing cemented in the hole.

After reviewing available information it is my feeling that 130' of 8 5/8" casing would provide adequate protection of the fresh and useable water in this area.

L. Kristopher Moore istopler Moore

Hydrologist