

2 030387

15-155-02839-0000

API NUMBER 15- Comp. 1-11-1935

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C SE NW, SEC. 35, T 23 S, R 4 (W)

3300' feet from S section line

3300' feet from E section line

TECHNICIAN'S PLUGGING REPORT *JK, JK*  
Operator License # 5271-9728

Lease Name Goering B Well # 7

Operator: S & K Oil Company

County Renov 109.56

Name & Address P.O. Box 559

Well Total Depth 3371' feet

Julsa, Ok. 74101

Conductor Pipe: Size 15 1/2" feet 217' / 225sx

Surface Casing: Size 8 5/8" feet 3260' / 250sx

Abandoned Oil Well  Gas Well  Input Well  SWD Well  D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Gressell Oil Field Service License Number 5823

Address Box 607, Burrton, Ks. 67020

Company to plug at: Hour: 08:00 Day: 21 Month: 3 Year: 19 86

Plugging proposal received from Eddie Gressell

(company name) Gressell Oil Field Service (phone) \_\_\_\_\_

were: Bod hole could not get to bottom, run 1" inside and outside 8 5/8" csg. as far as possible, pump cement to surface

RECEIVED  
STATE CORPORATION COMMISSION

APR 11 1986 4-11-86

CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Dist. #2 Office  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 12:50 Day: 26 Month: 3 Year: 19 86

ACTUAL PLUGGING REPORT ran 1" inside 8 5/8" 220', outside 8 5/8" to 300'

Halliburton Services) # 361131-1 pumped 115 cu. inside 8 5/8" csg., pumped 260 cu outside 8 5/8" csg. 3-22-85 pumped 175 cu, 200# bulls outside 8 5/8" csg. to surface. let set. ck. well later cement down hole outside 8 5/8" 3-26-86 Haven Redi-mix dumped 2 yds sand mix to surface outside 8 5/8" casing.

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(did/did not) observe this plugging.

APR 11 1986

DATE \_\_\_\_\_

Signed Don Thompson  
(TECHNICIAN)

INV. NO. 13380

3-26