

*R*

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION 25/8 - 11/8 - 2E/4

SEC. 31 TWP. 10 RGE. 11-W

Dry Hole X Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 2 Lease N.C. Johnson

Operator The Henderson Oil Co Address 502 - DePue Bldg Wichita - Kans.

Field \_\_\_\_\_ County Barber

Total Depth 3377 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 8 1/2 - 312 ft. Circulated with cement.  
5/8 casing at 3373 ft. cemented with 95 sacks cement.  
Plugged back to 3360 ft. with chat. Dumped  
5 sacks of cement at 3360 ft. Shot off & pulled  
the 5/8 casing. Mud to 300 ft. Set Rock Bridges &  
15 sacks of cement at 300 ft. Mud to 30 ft.  
Plug to 10 sacks of cement at the surface.

RECEIVED  
STATE CORPORATION COMMISSION

MAR 19 1951

CONSERVATION DIVISION  
Wichita, Kansas

E. W. Stouck  
District Conservation Agent

Date 3-19-51

**PLUGGING**  
FILE SEC-31 T-10 R-11W  
BOOK PAGE 67 LINE 40

*X*