

1 070163

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 083-21,244-0600  
150' NE of C NW NE, SEC. 2, T. 24, S, R. 24 WEX

4726 feet from S section line  
1874 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4808  
Operator: Smokey Oil Company  
Name & Address: P. O. Box 2360  
Casper, WY 82602

Lease Name Schraeder Well # 31-2  
County Hodgeman 157.30  
Well Total Depth 4840 Mississippi feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 477

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor True Drilling Company License Number 4708

Address P. O. Box 2360, Casper, WY 82602

Company to plug at: Hour: 8:00 am Day: 3 Month: April Year: 19 86

Plugging proposal received from Buzz Montgomery

(company name) True Drilling (phone) 307-237-9301

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2452 Anhydrite 1600

- 1st plug at the base of the Anhydrite with 50 sx cement
- 2nd plug 30' below the base of the surface pipe with 50 sx cement.
- 3rd plug solid bridge hulls - plug at 40' -- cement to surface with 10 sx cement
- 5th plug to circulate rathole with 10 sx cement
- 6th plug to circulate mouse hole with 10 sx cement

Plugging Proposal Received by Don C. Ubel (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part None

Operations Completed: Hour: 11:00 am Day: 3 Month: April Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 1620' with 50 sx cement, 2nd plug at 507' with 50 sx cement, 3rd & 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 5th plug to circulate rat hole with 15 sx cement, 6th plug to circulate mouse hole with 10 sx cement.

STATE CORPORATION COMMISSION

APR - 7 1986

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.

(If additional description is necessary, use BACK of this form.)

4-7-86

INVOICED (if you do not observe this plugging.)

Signed Dan Goodrow (TECHNICIAN)

DATE APR 7 1986

INV. NO. 13303 43

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

19-093-21244-0000

Starting Date March 21 1986 month day year

API Number 15-083-21,244-427 150' NE of C NW NE Sect 2 Twp. 24 S, Rg 24 East 4726 Ft. from South Line of Section 1874 Ft. from East Line of Section

OPERATOR: License # 4808 Name Smokey Oil Company Address P. O. Box 2360 City/State/Zip Casper, WY 82602 Contact Person C. F. Pickard Phone (307)-266-0230

Nearest lease or unit boundary line 554 feet County Hodgeman Lease Name Schraeder Well # 31-2 Ground surface elevation 2452 feet MSL

CONTRACTOR: License # 4708 Name True Drilling Company City/State Casper, WY 82602

Well Drilled For: X Oil SWD Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 1 X 2 Depth to bottom of fresh water 200 Depth to bottom of usable water 450 Surface pipe planned to be set 475 Projected Total Depth 4750 feet Formation Mississippian

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

cementing will be done immediately upon setting production casing. Date Feb 12 1986 Signature of Operator or Agent C. F. Pickard Title Engineer

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 475 feet per Approved By 2-18-86

3-28-86 - Spud 3-29-86 set 477' of 8 1/2 BUZ Montgomery ne

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 50 sx Base Anhydrite feet depth with surf. csg. 50s of 2nd plug @ 50 sx 30' below base surf. csg. 50s of 3rd plug @ 10 sx 40' below surf. 50s of 4th plug @ 15 sx in rat hole 50s of 5th plug @ 10 50s of (2) Rathole with 10 50s (b) Mousehole with 50s

Table with columns: PUSHER (Dan), TD (4840), SURFACE PIPE (8 1/2 @ 477), ANHYDRITE (1600), STARTING TIME & DATE (4-3-86 8:00), COMPLETION TIME & DATE (11:00), 1st PLUG @ (1620 FT. W/ 50 SX), 2nd PLUG @ (507 FT. W/ 50 SX), 3rd PLUG @ (40 FT. W/ 10 SX), 4th PLUG @ (FT. W/ SX), RAT HOLE CIRCULATED W/ (15 SX), MOUSE HOLE CIRCULATED W/ (10 SX), WATER WELL PLUGGED W/ (N/A SX), CEMENT COMPANY (Hillabee Co), TECHNICIAN (Dan Gooden)

STATE CORPORATION COMMISSION APR - 7 1986 CONSERVATION DIVISION Wichita, Kansas