

1 080572

STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-055-20,682-0000C NW NW, SEC. 26, T 24 S, R 32 W/K4620 feet from S section line4620 feet from E section line

## TECHNICIAN'S PLUGGING REPORT

Operator License # 5363Lease Name Delbert Well # 1Operator: Berexco, Inc.County Finney 163.31Name & Address 970 Fourth Financial CenterWell Total Depth 5025 feetWichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 1890Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Beredco, Inc. License Number 5147Address 970 Fourth Financial CenterCompany to plug at: Hour: 10:00 p.m. Day: 27 Month: 11 Year: 1986Plugging proposal received from Gary Marshall(company name) Beredco Inc. (phone) 316-672-3074Elevation 2805'were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1600'1st plug at 3000' with 100 sx cement, 2nd plug at 1930' with 50 sx cement,3rd plug at 400' with 25 sx cement, 4th plug at 40' with 10 sx cement,5th plug to circulate rathole with 10 sx cement,6th plug to circulate mousehole with 10 sx cement.Plugging Proposal Received by Dan Goodrow  
(TECHNICIAN)Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None XOperations Completed: Hour: 3:30 a.m. Day: 28 Month: 11 Year: 1986ACTUAL PLUGGING REPORT 1st plug at 3000' with 100 sx cement,2nd plug at 1890' with 50 sx cement,3rd plug at 900' with 75 sx cement,4th plug at 40' with 10 sx cement,5th plug to circulate rathole with 15 sx cement,6th plug to circulate mousehole with 10 sx cement.Remarks: Used 60/40 Pozmix 6% gel by Dowell.INVOICED (If additional description is necessary, use BACK of this form.)  
I (did not) observe this plugging. DEC-3DATE 12-3-86INV. NO. 1548611-28CONSERVATION DIVISION  
Wichita, KansasSigned J. H. Mey  
(TECHNICIAN)FORM CP-2/3  
Rev. 01-84