

1 120327

10-20

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 055-20,820-0000

SE SE SE, SEC. 28, T 24 S, R 34 W/E

330 feet from S section line

330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5003

Lease Name Brown "B" Well # 1-28

Operator: McCoy Petroleum Corporation

County Finney 164.94

Name & Address 110 South Main, Suite 500

Well Total Depth 5075 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 1898

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Gibson Well Service License Number 5866

Address P.O. Box 1510, Liberal, KS 67905-1510

Company to plug at: Hour: 1:12 p.m. Day: 20 Month: 10 Year: 19 89

Plugging proposal received from Daryl Hanson

(company name) McCoy Petroleum Corporation (phone) 316-532-5452

were: 5 1/2" at 5071' PBD 5031' Perfs at 4774-4776'

1st plug set CIBP at 4650' with 3 sx cement on top,

2nd plug at 2000' with 50 sx cement,

3rd plug at 850' with 30 sx cement,

4th plug at 40' with 10 sx cement.

Plugging Proposal Received by Duane Rankin  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 2:45 p.m. Day: 20 Month: 10 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug set CIBP at 3155' with 3 sx cement on top,

Plugged through tubing: 10-24-89

2nd plug at 2001' with 50 sx cement,

3rd plug at 859' with 30 sx cement,

4th plug at 40' with 10 sx cement. OCT 24 1989

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. Recovered 2150' of 5 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

**INVOICED**

(XXX / did not) observe this plugging.

DATE 10-30-89

Signed Duane Rankin  
(TECHNICIAN)

INV. NO. 26271