

To: 1 080164  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15- 055-20,407-0002

J

SE NW NW, SEC. 7, T 24 S, R 34 W XX

4000 feet from S section line  
4020 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License / 5952  
Operator: Amoco Production Company  
Name & Address: P.O. Box 800, Room 924  
Denver, CO 80201

Lease Name Crawford Gas Unit A Well # 4HI  
County Finney 99.13  
Well Total Depth 3050 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 1616

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWO Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton Services License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 10 a.m. Day: 25 Month: 11 Year: 19 97

Plugging proposal received from Joe Eudey

(company name) Amoco Production Co. (phone) 316-356-6981

ware: 5 1/2" at 3050' w/560 sx cement, PBSD 2695', Perfs at 2607-30, 2545-70, 2490-2512, 2424-68  
CIBP at 2700'

1st plug pump down 5 1/2" with 500 lbs. hulls and 192 sx cement.

Check backside.

Plugging Proposal Received by Kevin Strube  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11 a.m. Day: 25 Month: 11 Year: 19 97

ACTUAL PLUGGING REPORT 1st plug pumped down 5 1/2" with 500 lbs. hulls and 200 sx cement.

Maximum pressure 50 psi. Hole loaded-shut down.

Pumped down 8 5/8" X 5 1/2". Pressured up to 500 psi.

12-4-97

RECEIVED  
DEC 11 10  
AM  
CORP

Remarks: Used 65/35 Class C Pozmix by Halliburton. No casing recovery.  
(If additional description is necessary, use BACK of this form.)

I (date) 12-8-97 hereby observe this plugging.

DATE 12-8-97

Signed Kevin D Strube  
(TECHNICIAN)

INV. NO. 49592