RASSAS

Form CP-3
Rev. 6-4-68

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

J. Lewis Brock
Administrator
P. O. Box 17027
Wichita, Kansas 67217

	Icer Addis		NSERVATION OF 1974	ED MMISSION	
Operator's Full Name	2002 110022		NSERVATION DIVISION CON RESERVATION DIVISION GT 202 " See STONE SE		
		Wichita, Kansas	6/202 53	/	_
Lease Name		·	Vell No. # 2		
Location	SW NW NE	Sec.	15 Twp. 16 Rge	11_(E)	_('
County	Barton	······	Total Depth	3364	
Abandoned Oil Well	Gas Well	Input Well_	SWD Well	D &	A
Other well as hereafte	er indicated				
Plugging Contractor					
Address	200 N. Main, V	Wichita, Kansas	License No	•	
Operation Completed:					
The above well was plu 8 5/8" csg. 213' C					
8 5/8" csg. 213' C	wc.	Or get plug &	displaced 40	eav comant	th
8 5/8" csg. 213' C	wc. h heavy mud to 480				
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to	wc. h heavy mud to 480 200° & displaced	25 sax cement	thru drill pip	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug	wc. h heavy mud to 480 200° & displaced , & displaced 10 s	25 sax cement	thru drill pipe Halliburton Co	e. Mud to	
8 5/8" esg. 213' Concentrated hole with drill pipe. Mud to	wc. h heavy mud to 480 200° & displaced , & displaced 10 s	25 sax cement	thru drill pipe Halliburton Co	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug	wc. h heavy mud to 480 200° & displaced , & displaced 10 s	25 sax cement	thru drill pipe Halliburton Co	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug	wc. h heavy mud to 480 200° & displaced , & displaced 10 s	25 sax cement	thru drill pipe Halliburton Co	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug	wc. h heavy mud to 480 200° & displaced , & displaced 10 s	25 sax cement	thru drill pipe Halliburton Co	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug Company's pump true	wc. h heavy mud to 480 200° & displaced . & displaced 10 s k, cementing to be	25 sax cement sax cement with ase of cellar.	thru drill pipe	e. Mud to	
8 5/8" csg. 213' C Circulated hole wit drill pipe. Mud to 1/2 sax hulls, plug	wc. h heavy mud to 480 200° & displaced . & displaced 10 s k, cementing to be	25 sax cement sax cement with ase of cellar.	thru drill pipe Halliburton Co	e. Mud to	