

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
266 N. Main St., Ste. 220  
Wichita, KS 67202-1513

API Well Number: 15-015-40335-00-00  
Spot: SWNWSE Sec/Twnshp/Rge: 35-25S-4E  
1499 feet from S Section Line, 2499 feet from E Section Line  
Lease Name: RICE-TANNER A Well #: 6  
County: BUTLER Total Vertical Depth: 2454 feet

Operator License No.: 33192  
Op Name: CROWN ENERGY COMPANY  
Address: 1117 N.W. 24TH ST.  
OKLAHOMA CITY, OK 73106

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	7	2400		0 SX
SURF	13	750		0 SX

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 07/08/2016 12:00 AM  
Plug Co. License No.: 31925 Plug Co. Name: QUALITY WELL SERVICE, INC.  
Proposal Rcvd. from: DAN FLOWERS/CROWN EN Company: CROWN ENERGY CO. Phone: (316) 321-0550

Proposed  
Plugging  
Method:

As Required

Plugging Proposal Received By: JONATHAN HILL Witness Type: COMPLETE (100%)  
Date/Time Plugging Completed: 07/11/2016 12:00 AM KCC Agent: JONATHAN HILL

Actual Plugging Report:

Perfs:

---7/8/2016:  
1) Dug out well and found 7" casing w/ head inside ~9" casing. Cement on backside on 9"  
2) Welded collar on 7", ran in hole w/ bailer and tagged bridge at 162' (fluid in hole). Pulled bailer  
3) Ran in hole w/ tubing and notched collar, broke through bridge. Ran tubing to 2387' and rigged up cement  
4) Pumped 50 sks Class A 60/40/4% cement w/ 3% CaCl & cedar fiber. Good returns to surface  
5) Pulled tubing out, ran in Excel Wireline (Pratt, KS) to 250' and perforated. Rig down and shut down for day.  
---7/11/2016  
1) Tagged bottom plug at 2300'  
2) Ran in tubing to 250' and pumped 350 sks Class A 60/40/4% cement w/ 3% CaCl. Circulated cement up 7" casing to surface. Pulled tubing  
3) Tied into 7" casing, and pumped 225 sks cement. Circulated cement up backside. Hole staying full.

Top	Bot	Thru	Comments
2420	2454		

Remarks: CEMENTING COMPLETED BY QUALITY WELL SERVICE, ELLINWOOD, KS. TICKET #: 6537

Plugged through: TBG

District: 02

Signed Jonathan Hill

(TECHNICIAN)

AUG 18 2016

*no*