

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-089-20, 191-00-01

SW, Sec. 10, T 16 S, R 11 W 1/4

330 feet from N 1/4 section line

1065 feet from W 1/4 section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5739

Lease Name Reddyche Well # 2-SAD

Operator: Pioneer Operations Co.  
Name &  
Address 410 Main, Russell, Ks. 67665

County Butler

Well Total Depth 525 feet 25.0'

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8" feet 239

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well X D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cementing Co. Inc. License Number \_\_\_\_\_

Address Box 31, Russell, Ks 67665

Company to plug at: Hour: 9:00 AM Day: 15 Month: 4 Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Fron Smith

(company name) Pioneer Operations Co. (phone) 913-483-3954

were: Order 250 lbs 2% permix - 6% Sol.

Signed [Signature]  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:00 AM Day: 15 Month: 4 Year: 1983

ACTUAL PLUGGING REPORT 8 5/8" - 239' S.P. case w/ 180 lbs. 5 1/2" set at 525' w/ 125 lbs.  
Plugged bottom w/ sand & cement to 300'. Top perf at 219'  
squeezed w/ 500 lbs. & followed w/ plug to 200'. Ran tubing to  
200' & ~~was~~ circulated cement to surface, pulled tubing & squeezed  
casing to 500 pounds pressure. Pumped 5 lbs cement in 8 5/8"  
pressure to 700 pounds.

Remarks: \_\_\_\_\_

I hereby certify that the above plugging instructions were given as herein stated  
and that I (did / ~~did not~~) observe this plugging.

RECEIVED  
STATE CORPORATION COMMISSION

Signed [Signature]  
(TECHNICIAN)

INVOICED

APR 18 1983  
4-18-83  
CONSERVATION DIVISION  
Wichita, Kansas

FORM CP-2/3  
Rev. 9-82

DATE 4-21-83

INV. NO. 4076-W