

TO:
 STATE CORPORATION COMMISSION
 CONSERVATION DIVISION - PLUGGING
 266 N. Main St., Ste. 220
 Wichita, KS 67202-1513

API Well Number: 15-055-00332-00-00
 Spot: NESW Sec/Twnshp/Rge: 29-22S-34W
1914 feet from S Section Line, 3322 feet from E Section Line
 Lease Name: OLTMANN Well #: 1
 County: FINNEY Total Vertical Depth: 2660 feet

Operator License No.: 33999
 Op Name: LINN OPERATING, INC.
 Address: 600 TRAVIS STE 5100
HOUSTON, TX 77002

String	Size	Depth (ft)	Pulled (ft)	Comments
CIBP		1100		
L1		2660		2484-2660 SLOTTED LINER
PROD 7		2490	0	WITH 100 SX CMT
SURF	10.75	325		WITH 200 SX CMT

Well Type: GAS UIC Docket No: _____ Date/Time to Plug: 08/24/2016 1:00 PM
 Plug Co. License No.: 33338 Plug Co. Name: ORR ENTERPRISES, INC.
 Proposal Rcvd. from: JAVIER Company: ORR ENTERPRISES, INC. Phone: (580) 251-9618

Proposed Plugging Method: 1). MIRUSU, attempt to unseat pump. And/or backoff rods as deep as possible (+/-2000'). 2). Unflange and NU BOP. POH w/tbg, if tbg is stuck, cut tbg above free point. 3). Circulate hole with mud and spot 60 sacks Class "C" cement. POH with tbg and WOC. Tag TOC. 4). Locate end of tbg @ 2000' and spot 40 sacks of cement. POH with tbg. 5). Pick up 7" tbg set CIBP and set at 1100'. Release tbg; load and test casing at 500 psi. 6). Rig up wireline and perf squeeze holes @ 1050'. Trip in hole with 7" packer @ 700'. Squeeze with 80 sacks cement with hulls in last 40 sacks. Wait on cement. POH with packer. 7). Perf squeeze holes @ 350', circulate cement to surface with +/- 200 sacks Class "C" cement. 8). RDMOSU. Cut and cap well.

Plugging Proposal Received By: KEN JEHLIK WitnessType: COMPLETE (100%)
 Date/Time Plugging Completed: 08/26/2016 10:00 AM KCC Agent: KEN JEHLIK

Actual Plugging Report:

Perfs:

PUMP 60 SX CMT AT 2575' THROUGH TBG. TAG TOC @ 2417' AFTER 15 HOURS.
 PUMP 40 SX CMT AT 2000'. SET CIBP @ 1100'. TEST CASING TO 500#. HOLDING.
 PERFORATE 4 HOLES AT 1050'. RUN TBG & PACKER TO 700'. INJECTION RATE 3
 BPM @ 300#. PUMP 50 SX CMT, 15 BALL SEALERS THEN 30 SX CMT. DISPLACE TO
 875' & PRESSURE TO 1000#, LEAVING 30 SX CMT INSIDE THE CASING & 50 SX CMT
 OUTSIDE THE CASING. PERFORATE 4 HOLES AT 350'. CIRCULATE CMT FROM 350'
 TO 0' WITH 200 SX CMT LEAVING BOTH 7" CASING & 7" X 10 3/4" ANNULUS FULL
 OF CMT.

Top	Bot	Thru	Comments
2524	2600		

Remarks: USED CLASS C COMMON CEMENT BY ORR ENTERPRISES.

Plugged through: TBG

District: 01

Signed _____

Ken Jehlik
 JA

(TECHNICIAN)

RECEIVED
 SEP - 1 2016
 KCC DODGE CITY

OCT 03 2016
 FORM CP-2/3