

15. 167. 01649. 00. 00  
WELL PLUGGING RECORD

DTA  
Survey

STATE OF KANSAS  
STATE CORPORATION COMMISSION

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division,  
State Corporation Commission,  
800 Bittling Building,  
Wichita, Kansas.

OR  
FORMATION PLUGGING RECORD

Strike out upper line  
when reporting plugging  
off formations.

NORTH

	32		

Locate well correctly on above  
640 A. Plat

RUSSELL County. Sec. 32 Twp. 15 Rge. 14 (W)

Lease Name BECKER  
 Lease Owner VERNON OIL & GAS COMPANY  
 Office Address FOURTH NATL. BANK BLDG.  
 Character of Well (Oil, Gas or Dry) DRY Total Depth of Well 3429 Feet  
 Date, well, completed AUGUST 11 1935  
 Application for plugging and log of well filed VERNON OIL & GAS COMPANY 1935  
 Application for plugging approved AUGUST 12 1935  
 Plugging Commenced AUGUST 13 1935  
 Plugging Completed AUGUST 16 1935  
 Reason for abandonment of well or producing formation HOLE FULL OF WATER IN SICILEOUS LIME

If a producing well is abandoned, date of last production \_\_\_\_\_ 193\_\_\_\_  
 Was permission obtained from the Conservation Division or its agents before plugging was commenced? YES

Name of Conservation Officer who supervised plugging of this well \_\_\_\_\_  
 Producing formation \_\_\_\_\_ Depth to top \_\_\_\_\_ Bottom \_\_\_\_\_  
 Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				15 1/2"	431'	431'
				12 1/2"	702'	702'
				10"	933'	933'
				8"	2861'	2861'
				6 5/8"	3390'	3390'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

Used buckets to pull mud from slush pond and filled to bottom of 65/8" casing, then unseated and pulled 65/8" casing, and filled with mud to 3040', then pulled 8", 10", and 12 1/2" casing and bridged the hole at 450', then pulled the 15 1/2" casing and filled the hole to the surface with mud.

**PLUGGING**  
 FILE SEC 32 T15 R 14 W  
 BOOK PAGE 13 LINE 47

(If additional description is necessary use BACK of this sheet)

Does the above conform strictly to the Conservation Division regulations? \_\_\_\_\_  
 Was exception made? \_\_\_\_\_ If so describe \_\_\_\_\_  
 Correspondence regarding this well should be addressed to VERNON OIL & GAS COMPANY  
 Address FOURTH NAT'L BANK BLDG., WICHITA, KANSAS

STATE OF KANSAS COUNTY OF RUSSELL, ss.

N. A. WOODS (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) N. A. Woods  
Clearwater Kansas  
 (Address)

SUBSCRIBED AND SWORN to before me this 23 day of August, 1935

My commission expires March 19, 1938  
L. B. Gardner  
 Notary Public.

VERNON OIL & GAS COMPANY  
 204 Fourth National Bank Bldg.,  
 Wichita, Kansas.

RECEIVED  
 AUG 13 1935  
 BY *me*

*2*

Log of Becker #1, located in NE cor., NE $\frac{1}{4}$  of Sec. 32, Twp 15, Rge 14W, Russell County, Kansas. ✓

Company - Vernon Oil & Gas Company  
 Contractor - I. W. Murfin  
 Completed - August 11, 1935.

PLUGGING  
 FILE SEC 32 T 15 R 14 W ✓  
 BOOK PAGE 12 LINE 12

Surface	35	Shale	1740
Clay	40	Red Rock	1750
Black Slate	65	Lime Shells	1780
Blue Shale	240	Lime-S.Gas (250,000)	1785
Gray Shale	255	Lime Broken	1800
Brown Shale	260	Lime	1860
Red Rock	265	Red Rock	1880
Gray Shale	270	Lime Sandy	1895
Red Rock	300	Lime Sandy	1920
Brown Shale	365	Blue Shale	1925
Water Sand - 1/2BW	368	Lime	1990
Blue Shale	380	Sand Hard	2015
Iron Hard	395	Shale	2025
Blue Mud	400	Lime	2050
Water Sand	410	Blue Shale	2055
Sandy Shells Water	430	Lime	2080
Sandy Shale	435	Shale	2085
Brown Shale	441	Lime	2095
Blue Shale	460	Shale	2100
Water Sand	485	Lime	2120
Shale Blue	495	Shale	2125
Water Sand	525	Lime Sandy	2145
Iron Pyrite	530	Red Rock	2150
Sand	555	Shale Brown	2190
Iron Lime	560	Lime	2200
Red Rock	630	Shale Brown	2225
Red Rock	927	Red Rock	2235
Anhydrite Lime	950	Lime Hard	2245
Anhydrite	966	Lime Light	2250
Red Rock	1045	Lime	2300
Red Rock	1085	Blue Shale	2305
Lime	1095	Lime	2320
Red Rock	1140	-----	2325
Slate	1155	Shale Blue	2330
Lime	1165	Lime	2335
Blue Shale	1190	Lime	2348
Red Rock	1240	Shale	2353
Shale Blue	1260	Lime	2363
Slate Blue & Shells	1305	Broken Lime & B.Shale	2390
Lime Shells	1315	No Log	2407
Lime Hard	1320	Shale	2412
Blue Shale	1340	Lime	2417
Lime Salt	1370	Shale	2424
Salt	1610	Shale	2440
Lime	1615	Lime	2445
Slate	1620	Shale & Shells	2475
Lime	1630	Lime Broken	2490
Shale Blue	1635	Shale & Shells	2515
Shells	1660	Red Rock	2521
Red Rock	1665	Shale Blue	2550
Lime	1685	Lime	2555
Shale Blue	1690	Shale	2560
Lime	1710	Shale	2575
Red Rock	1720	Lime	2595
Lime	1735		

VERNON OIL & GAS COMPANY  
 204 Fourth National Bank Bldg.,  
 Wichita, Kansas  
 August 12, 1935.

Log of Becker #1, located in NE cor. NE 1/4 of Sec. 32- Twp15, Rge 14W,  
 Russell County, Kansas.

Company - Vernon Oil & Gas Company  
 Contractor - I. W. Murfin  
 Completed - August 11, 1935.

Shale	2635	Good showing of free oil	
Lime	2650	and water	3405-07
Shale	2655	Tested 3B oil and 3B water	
Lime	2660	in 5 hours	
Shale	2675	Showing of free oil	3309-12
Lime	2695	100' of water	3416-23
Shale	2700	1000' of water	3423-29
Lime	2705		
Broken Lime	2745	T. D.	3429
Shale	2775		
Lime	2800	D & A	
Shale	2805		
Lime	2825		
Shale	2845	CASING RECORD	
Shale	2848	15" 431	
Lime	2880	12 1/2" 702	
Lime	3080	10" 933	
Shale	3083	8" 2861	
Lime	3115	6-5/8" 3390	
Shale	3120		
Green & Blue Shale	3130		
Shale	3144		
Lime	3150		
Shale	3155		
Lime	3227		
1 BW	3190		
Shale	3235		
Lime	3262		
8" casing set at	2861		
Lime	3320		
Showing of oil	3310-13		
Shale	3324		
Lime	3350		
Showing of oil	3345-50		
Shale	3357		
Lime	3372		
Shale	3377		
Lime	3383		
Shale	3386		
Conglomerate	3390		
6 - 5/8" casing	3390		
Showing of oil	3390-93		
Lime	3395		
Shale	3397		
Lime	3423		
Sandy Lime HFV	3429		

PLUGGING  
 FILE SEC 32 T15 R 14W  
 BOOK PAGE 18 LINE 47