

To: 6 061697  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

10-25  
API NUMBER 15-009-07542-0000  
SE \_\_\_\_\_, SEC. 18, T. 16 S, R. 11 W/E  
2310 feet from S section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5245

2310 feet from E section line

Lease Name Redetzke Well # 3

Operator: Okmar Oil Co.  
Name & Address: Box 723  
Hays, Ks. 67601

County Barton 106.86

Well Total Depth 3288 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 330

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Okmar Oil License Number \_\_\_\_\_

Address Box 723 Hays, Ks.

Company to plug at: Hour: 2:00PM Day: 25 Month: Oct Year: 19 88

Plugging proposal received from Ted Crawford

(company name) Okmar Oil (phone) \_\_\_\_\_

were: Order 2 RECEIVED STATE CORPORATION COMMISSION 60/MISSION 6% Gel 5 sks Hulls.

10V 21 1988 11-21-88

CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Gilbert G. Scheck (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 2:30PM Day: 25 Month: Oct Year: 19 88

ACTUAL PLUGGING REPORT 8 5/8" set at 330' w/cwc sks. 5 1/2" set at 3287' w/150 sks. Top perf at 3162'. Pumped in 5 1/2" 25 sks cement followed w/4 sks Hulls in 100 sks cement w/500 psi. Pumped in 8 5/8" 1 sk Hulls in 75 sks cement w/400 psi. Shot hole in casing at 770'.

Remarks: B. J. Titan  
(If additional description is necessary, use BACK of this form.)

(If applicable, observe this plugging.)

Signed [Signature] (TECHNICIAN)  
Gilbert G. Scheck

INVOICED

DATE 11-29-88

INV. NO. 23158

# Perforators

INCORPORATED

QUALITY

LOGGING

SERVICE

COMPANY INDEPENDENT LEASE MGMT. COMPANY

WELL REDETZKE NO. 3

FIELD KRAFT-FRUSA

COUNTY BARTON STATE KANSAS

LOCATION:

NW NW SE

SEC. 18 TWP. 16S RGE. 11W

OTHER SERVICES:

PERMANENT DATUM: WELDED COLLAR 1865  
 LOG MEASURED FROM 1865 4 FT. ABOVE PERM DATUM  
 DRILLING MEASURED FROM KELLY BUSHING 1869

PLAN. S.B. 1869  
 D.F. 18  
 C.L. 18

DATE 2/2/61  
 RUN NO. ONE  
 TYPE LOG G/R N/N  
 DEPTH-DRILLER  
 DEPTH LOGGER 3246  
 BOTTOM LOGGED INTERVAL 3245  
 TOP LOGGED INTERVAL 2600  
 TYPE FLUID IN HOLE WATER & OIL  
 SALINITY PPM CL.  
 DENSITY LB./GAL.  
 TEMPERATURE 1100  
 MAN. REC. TIME 1 1/2 HR.  
 DR. REC. TIME  
 RECORDED BY SNYDER  
 WITNESSED BY MR JEWETT

RUN NO.	BIT	BORE HOLE RECORD		SL. FT.	CASE RECORD	FROM	TO
		FROM	TO				
1	12 1/2	0	330	8 5/8		0	330
2	8 7/8	0	3290	5 1/2	14	0	3290

NEUTRON  
 ONE  
 RUN NO. N/N  
 LOG TYPE RGN 308  
 TOOL JOINT NO. 3  
 DEPTH MODEL NO. N100  
 TYPE Scint  
 LINK ID. 2"  
 SOURCE MODEL NO. 300-308  
 SERIAL NO. 176227  
 SIZING 16"  
 CALIBRATION RA-BE  
 STANDARD 30 Omc

ONE  
 RGN 308  
 3"  
 G100  
 Scint  
 3"  
 8  
 H-1  
 R102

LOGGING DATA

DEPTH	API N. UNIT	SENS.	DIV. I OR R	PER LOG DE	PER LOG DE
52600	R3	200			
25					
4					
600					
LI					

RECEIVED  
 STATE CORPORATION COMMISSION

11 \* 7 1961  
 CONSERVATION DIVISION  
 Wichita, Kansas

MMA-RAY

DEPTH

NEUTRON