

To:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-083-21,123-0000NW/4, Sec. 18, T 22 S, R 24 W/EX330 feet from N/X section line330 feet from W/X section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5267Lease Name Schmitt "C" Well # 1Operator: K & E Petroleum, Inc.County HodgemanName & 100 S. Main, Suite 300 Hardage CenterAddress Wichita, KS 67202Well Total Depth 4775 feetConductor Pipe: Size feetSurface Casing: Size 8 5/8 feet 702Abandoned Oil Well Gas Well Input Well SWD Well D&A XOther well as hereinafter indicated Plugging Contractor Abercrombie Drilling, Inc. License Number 5422Address 801 Union Center, Wichita, KS 67202Company to plug at: Hour: 3:00 pm Day: 12 Month: February Year: 1984VERBAL PLUGGING ORDERS GIVEN TO Harvey Moore(company name) Abercrombie (phone) 316-262-1841were: to fill hole with heavy mud and spot cement through drill pipe.1st plug at 1660' with 50 sx cement2nd plug at 750' with 40 sx cementsolid bridge3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement5th plug to circulate rathole with 10 sx cement6th plug to circulate mousehole with 10 sx cement

Signed

Richard W. Lacy
(TECHNICIAN)Plugging Operations attended by Agent?: All Part None XOperations Completed: Hour: 5:00 pm Day: 12 Month: 2 Year: 1984

ACTUAL PLUGGING REPORT 1st plug at 1660' with 50 sx cement, 2nd plug at 750' with 40
sx cement, 3rd plug and 4th plug - solid bridge - hulls - plug at 40' -- cement to
surface with 10 sx cement, 5th and 6th plugs to circulate rathole and mousehole with
10 sx cement each.

Remarks: Use 60/40 Pozmix with 2% gel 3% cc by Sun Cementing.

RECEIVED
STATE CORPORATION COMMISSION
FEB 15 1984
CONSERVATION DIVISION
Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated
and that I (~~did~~) did not) observe this plugging.

Signed

Richard W. Lacy
(TECHNICIAN)

FORM CP-2/3
Rev. 9-82

INVOICED

DATE 2-23-84INV. NO. 0341