STATE OF KANSAS STATE CORPORATION COMMISSION

Form CP-4

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
P. O. Box 17027
Wichils, Kappas C. 277

WELL PLUGGING RECORD

NORTH Kingman County, Sec. 11 Twp. 30S Rgc. 10 Location as "NE/CNW#SW#" or footage from lines. C = NW NW Lease Owner. W. C. Bradley Lease Name. Katzer Office Address. 1009 Union Center, Wichita, Kans Character of Well (completed as Oil, Gas or Dry Hole). Dry Hole Date well completed. May 8,	
I lease Name Katzer Office Address 1009 Union Center, Wichita, Kans Character of Well (completed as Oil, Gas or Dry Hole) Date well completed May 8.	
Office Address 1009 Union Center, Wichita, Kans Character of Well (completed as Oil, Gas or Dry Hole) Date well completed May 8.	Well No. 7
Character of Well (completed as Oil, Gas or Dry Hole) Date well completed May 8	
Date well completed May 8.	
	19_72
Application for plugging filed Verbal Application	19
Application for plugging approved Verbal Approval	19
Flugging commenced May 8,	19.72_
Plugging completed May 8,	19.72_
Reason for abandonment of well or producing formation	
If a producing well is abandoned, date of last production.	
Locate well correctly on above Section Plat Was permission obtained from the Conservation Division or its agents before the Conservation Division Division or its agents before the Conservation Division Divis	e plugging was com-
Name of Conservation Agent who supervised plugging of this well G. R. Biberstein	
Producing formation Total Depth of W	Vall 4 . 755 Foot
Show depth and thickness of all water, oil and gas formations.	CHLINE CCL
OIL, CAS OR WATER RECORDS CA	ASING RECORD
FORMATION CONTENT FROM TO SIZE PUT IN	PULLED DUT
8-5/8" 245'	None
	
Filled hole with heavy rotary mud from 4,755 feet (rotary total depth) to 230 feet. Set plug at	
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement.	th
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug	th
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole.	
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole.	
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole.	
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. State Corporation	
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CORP	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONTROL OF THE CONTROL OF TH	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONTROL OF THE CONTROL OF TH	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONTROL OF THE CONTROL OF TH	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONTROL OF THE CONTROL OF TH	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CORP	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONTROL OF THE CONTROL OF TH	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement. 2 sacks cement in rathole. SIMPLE CORPORATION CONSTRUCTION OF CONSTRU	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CO. CONSERVATION DIVISION DIVISION MICHINE, Kannes of Plugging Contractor H-30. Inc. (II additional description is necessary, use BACK of this sheet) Name of Plugging Contractor H-30. Inc.	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CO. CONSERVATION DIVISION DIVISION MICHINE, Kannes of Plugging Contractor H-30. Inc. (II additional description is necessary, use BACK of this sheet) Name of Plugging Contractor H-30. Inc.	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and demented with 35 sacks dement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and demented to cellar with 10 sacks dement, 2 sacks dement in rathole. SIMPLE RECEIVE CONSERVATION DIVISION WICHIGAN TO NOTE TO	D
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORPORATION CONSERVATION TO THE CONSERVA	OA,
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE OF LONG TO THE SECOND TO THE S	MMISSION ON
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mid from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIATE RECEIVE CONSERVATION OF WICHIES REPORT WINCHIES REPORT WINCHIES REPORT WITH A 10 10 10 10 10 10 10 10 10 10 10 10 10	MMISSION ON
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIATE RECEIVE CONSERVATION OF WIGHING RECEIVE CONSERVATION OF WICHING RECEIVE CONSERVATION C	MMISSION ON
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIATE RECEIVE CONSERVATION OF WIGHING RECEIVE CONSERVATION OF WICHING RECEIVE CONSERVATION C	MMISSION ON
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIMPLE CORPORATION CONSERVATION DIVISION WICHING WAY CONSERVATION DIVISION Name of Plugging Contractor H-30, Inc. Address 200 No. Main, Wichita, Kansas 67202 STATE OF Kansas Dean Britting, Agent XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	MMISSION ON The above-described and the log of the
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and demented with 35 sacks dement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and demented to cellar with 10 sacks dement, 2 sacks dement in rathole. STATE OF RECEIVE WITCHIST AGENTALION Name of Plugging Contractor H-30, Inc. Address 200 No. Main, Wichita, Kansas 67202 STATE OF Kansas Dean Britting, Agent RECEIVE Sedgwick Section on oath, says: That I have knowledge of the facts, statements, and metters herein contained above distributed well as filed and that the same are true and correct. So help the God. (Signature) Main, Wichita, Kansas Michita, Main, Withita, Kansas Michita, Kansas Michita, Main, Withita, Kansas Michita, Michita, Kansas Michita, Kansas Michita, M	f the above-described and the log of the
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mid from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIME RECEIVE CORNER OF THE CORNER OF	f the above-described and the log of the
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mid from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. SIME RECEIVE CORNER OF THE CORNER OF	f the above-described and the log of the
4,755 feet (rotary total depth) to 230 feet. Set plug at 230 feet and cemented with 35 sacks cement. Filled hole with heavy rotary mud from 230 feet to 40 feet. Set solid plug at 40 feet and cemented to cellar with 10 sacks cement, 2 sacks cement in rathole. STATE CORE CELVE CONSERVATION DAY WIGHING TON DAY WIGHING TON DAY Name of Plugging Contractor H-30, Inc. Address Name of Plugging Contractor H-30, Inc. STATE OF Kansas Dean Britting, Agent well, beingklight duty about on oath, says: That I have knowledge of the facts, statements, or meters herein contained above description will be facts, statements, or meters herein contained above description will as filed and that the same are true and correct. So help the Cod. (Signature) 200 No. Main, Wichita, Kan (Address)	f the above-described and the log of the

15-095-20276-0000

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU -- KANSAS WELL SAMPLE BUREAU KANSAS GEOLOGICAL BOCIETY BUILDING 508 EAST MURDOCK - WICHITA, KANSAS

TOLDERE . D . W YMAHOD

BEC. 22 T. 300 P. 108 LOC. C . NA NA

FARM MODER

NO. 9

TOTAL DEPTH 3, 755*
COMM. 1982.1 25 3972 SHOT OR TREATED

COMP. 1072 0, 1972

COUNTY ESTE KANSAS

CONTRACTOR 13-30, IIIO

CASING

20 10 15

8 -5/8" 245" comented tr/250 axa comentelevation 1,731 KB

12

FIGURES, INDICATE BOTTOM OF FORMATIONS

227 Surface Soil Minds and think Recibed Shale end Mae . Shale and Shells Shale and Line Line and Shale Line Limo and Shale Chert and Lilay Chert I.L. Com 3 re Shalo and Line Sandstona Sandatone and Line Limo Notary Total Injih

STATE CORPORATION COMMISSION MAY 1 8 1972 CONSERVATION DIVISION

I hereby cortify the chare and foregoing to be a true and correct log of the above described well as these by the chilling reports.

H-30. 176.

State of Knimus

County of Sedgmiok

Subscribed and Swom to before me a notary Public in and for seld county and state this 17th. day of May. 1972

vicks commission Emplement

William Refers

June 50, 1974