

Sinclair Prairie Oil Co
Well Log

Selma Seyfert-A #8
NE SE NE, Sec. 29-16-11W, Barton Co., Kas
330' from North & East lines
Elevation 1906'

Harbar Drlg Co. rotary
Began drlg 8/11/1943
Comp. " 8/26/1943
T.D. 3389' in Arbuckle lime.
Dry Hole

Drillers Log

Surface Soil	25
Sand & Shells	110
Shale & Shells	225
8-5/8" set at 324'	
Lime	250
Shale & Shells	520
Shale	670
Red Bed	760
Anhydrite	795
Shale & Lime	1075
Shale & Shells	1210
Shale	1220
Shelly Salt	1350
Shale	1445
Lime Shells, Shale	1460
Shale & Lime	1585
Lime	1610
Shale	1620
Shale, Lime Shells	1730
Shale & Lime	1875
Sand-Pyrite	1887
Lime	1930
Lime & Shale	1975
Lime-broken	2050
Lime	2080
Shale & Lime Shells	2185
Shale & Lime	2235
Lime Shale & Shells	2305
Shale & Lime	2530
Lime	2590
Shale & Lime	2660
Lime	2755
Lime & Shale	2815
Lime, pyrites iron	2845
Lime	2900
Shale	2912
Lime	2945
Shale & Lime	2995
Lime Shells, Shale	3050
Lime	3184
Lime, soft	3198
Lime	3361
Chert & Lime	3369
Lime	3389 TD

5 1/2" set at 3364' rig floor.

Meas. -	Rig Floor -	Surface Level
Top Topeka Chert	2730	2727 1/2'
Lan. Kc	3075	3072 1/2'
Conglomerate	3350	3347 1/2'
Arbuckle	3364	3361 1/2'
T.D.	3389	3386 1/2'

FILE 29-16-11W
BOOK PAGE 90-41