This form shall be filed in duplicate with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ten days after the completion of the well, regardless of how the well was completed.

Attach separate letter of request if the information is to be held confidential. If

confidential, only file one copy. Information on side one will be of public record and

side two will then be held confidential.

Circle one: Oil, Gas Dry SWD, OWWO, Injection. Type and complete ALL sections.

Applications must be filed for dual completion, commingling, SWD and injection, T.A.

Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.).

KCC # (316) 263-3238. (Rules 82-2-105 & 82-2-125)

OPERATOR Maguire Oil Company	API NO. 15-145-20886 - 0000							
ADDRESS 4200 First National Bank Bldg.	COUNTY Pawnee							
	FIELD Wildcat							
**CONTACT PERSONJohn_C. Kelley PHONE 214/741-5137	PROD. FORMATION none							
PURCHASER none	LEASE Lippoldt							
	WELL NO. 1							
ADDRESS	WELL LOCATION C-NW-SE							
DRILLING KAW Drie Co. Inc	1980 Ft. from South Line and							
CONTRACTOR	1980 Ft. from East Line of							
ADDRESS 1010 Union Center	the SRC. 22 TWP . 228 RGE .19W							
Wichita, KS 67202	WELL PLAT							
PLUGGING Kelso Casing Pulling	KCC							
CONTRACTOR ADDRESS Box 176, Chase, Kansas	KGS (Office Use),							
TOTAL DEPTH 4800' PBTD 3850'	22							
SPUD DATE 6/26/81 DATE COMPLETED 1/9/82	x							
ELEV: GR 2218' DF KB								
DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS								
Amount of surface pipe set and cemented874'	DV Tool Used? no							
AFFIDAVI	<u>T</u>							
STATE OF Texas , COUNTY OF]	Dallas SS, I, John C.							
Kelley OF LAWFUL AGE, BI	EING FIRST DULY SWORN UPON HIS OATH,							
DEPOSES THAT HE IS Engineering Ass't (FOR)(OF) Maguire Oil Company							
OPERATOR OF THE Lippoldt LEASI	E, AND IS DULY AUTHORIZED TO MAKE							
THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERATOR	OR, THAT WELL NO. 1 ON							
SAID LEASE HAS BEEN COMPLETED AS OF THE 9 DAY								
ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID	WELL IS TRUE AND CORRECT. 4-82							
FURTHER AFFIANT SAITH NOT.	Jel a deal							
-	(S) John C. Kelley							
SUBSCRIBED AND SWORN BEFORE ME THIS DAY O	F February , 19 82							
	Janelle Allen							
MY COMMISSION EXPIRES: 2/14/95	NOTARY SPUBLIMATION COMMISSION							
**The person who can be reached by phone regarding mation. Within 45 days of completion, a witnessed	any questions concerning this pator- initial test by the Commission is							
mation. Within 45 days of completion, a witnessed required if the well produces more than 25 BOFD or	is located in a Basic Oraldon (1970)							

NAME

SIDE TWO

WELL: LOG

FORMATION DESCRIPTION, CONTENTS, ETC.

Show all important zones of parasity and contants thereof; cared intervals, and all drill-stem tests, including depth interval tested, cushion used, timo tool open, flowing and shut-in pressures, and recoveries.

TOP

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

DEPTH

FORMATIO	N DESCRIPTION, C	ONTENTS, ETC.		102		BOTTO	*	NAME		DEFIN	
Shell & Shal Shale Lime & Shale Shale Lime & Shale Lime	Lime & Shale Shale Lime & Shale			0 2214 3030 3285 3771 4085 4455 4707		3029 3284 3770 4084 4454 4706 4800 T.D		Anhydrite Heebner Lansing Swope Bs. Kansas Ci Cherokee Mississippi D. Kinderhook Arbuckle T.D.		1240' 3721' 3825' 4053' 4133' 4282' 4365' 4424' 4765' 4800'	
J							İ			,	
				Ì							
	•										
	,										
					\cdot						
	•	•	•		ĺ		- [
			•								
			•				,				
Report of all string	35 Set — surface,	intermediate,	production, et	c. CASING	REC	ORD	(New)	or (Used	——! :)		
Purpose of string	Size hole drilled	Size cosing set	Weight lbs/ft.	Setting depth		Type cem		Sacks		ond percent odditives	
Surface	12½"	8-5/8"	24#	874	50/	/50 Pc	z Mis	350	3%	Gel c.c.	
Production	7-7/8"	5 <u>1</u> 511	15.50#	44321				150	10% Salt 75% CFR-2		
	-	<u> </u>									
	PERFORATION RECORD										
Top, ft.	Bottom, .ft.	Socks co	ement		perfi	t.	Sla	e & type		enth Interval 9 - 4334 .	
	TUBING RECO	RD	•		1				405	5-4062'	
Sixe	Setting depth	Packer 1	er at	*	2 2					<u>8-4030 ' </u>	
ACID, FRACTURE, SHOT, C				*4				3962-3966' 3898-3930'			
		int and kind of		CEMENT 30	UEEZ	E RECO	-KD			Val treated	
				. <u>. </u>				4329-			
700 gals Dowe	_		ulsifyer	,				4055-			
Date of first production	ing, pumping,	g, pumping, gas lift, etc.)				RECEIVED ATE OF PORATION COMMISSION					
	NONE WEL		Gas			<u> </u>	<u></u>	Gravit	y ""	TON CHAMARAIN	
PER 24 HOURS Disposition of gas (ventee		bb		<u> </u>	MCF	· ·	<u> </u>	bbls.		4 1989 _{CFPB}	
	, ward on lease or	loig /				Perf	oratio	ons Gang	ERVATI Ichlia	ON DIVISION	
*all perforat	ions have	C.I.B.P.	w/5 sxs	cement	abo	ve th	em, w	/top plug	@ 38	850'.	