

15.081.10.117.00.00

Form CP-3
Rev. 6-26-62

KANSAS
STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

J. P. Roberts
Assitant Director
500 Insurance Building
212 North Market
Wichita 2, Kansas

RECEIVED
STATE CORPORATION COMMISSION

NOV 6 1963

CONSERVATION DIVISION
Wichita, Kansas

Operator's Full Name Frank J. Black

Complete Address: Box 150 Mc Pherson, Kansas

Lease Name C.R. Anton Well No. A-1

Location N/2 S^W Sec. 18 Twp. 30 Rge. 33 (E) (W)

County Haskell Total Depth 5000'

Abandoned Oil Well X Gas Well Input Well SWD Well D & A X

Other well as hereafter indicated:

Plugging Contractor: Knight Casing Pulling Service

Address: Chase, Kansas License No. 436

Operation Completed: Hour 1 PM Day 4- Month 11 Year 63

The Above well was plugged as follows:

8 5/8"-738' Circulated w/cement, 5 1/2"-4999' Cemented. Plug back to 4180'

Plug bottom w/sand and 15 Sax.cement 4180' to 4070' Mud 4070' to 700'

35 Sax.cement 700' to 600' Mud 600' to 50'

Rock bridge 50' to 40' 15 Sax.cement 40' to surface.

Company Pump. Pulled 2500' 5 1/2" Pipe.

I hereby certify that the above well was plugged as herein stated.

INVOICED

Signed: [Signature]
Well Plugging Supervisor

DATE 11/8/63
INV. NO. 8046-W

15.081-10117-0000
PAN AMERICAN PETROLEUM CORPORATION

WELL RECORD

SUPPLEMENTAL
(ENTER "X" WHEN APPLICABLE)

LOCATE WELL CORRECTLY

LEASE C. R. Anton "A" WELL NO. 1

LOCATION OF WELL: 1980 FT. NORTH SOUTH OF THE 1980 FT. SOUTH LINE AND 1980 FT. EAST WEST OF THE WEST LINE OF THE 1/4 1/4 SU 1/4

OF SECTION 18 TOWNSHIP 30 NORTH SOUTH, RANGE 33 EAST WEST.

Maskell COUNTY Kansas STATE

ELEVATION: Ground 2953 ROB 2963

COMPLETED AS: OIL WELL GAS WELL WATER WELL DRY HOLE

DRILLING COMMENCED 11-1 19 62 COMPLETED 11-13 19 62

OPERATING COMPANY Pan American Petroleum Corporation ADDRESS Box 507, Ulysses, Kansas

OIL OR GAS SANDS OR ZONES

NAME	FROM	TO	NAME	FROM	TO
<u>1 Des Moines</u>		<u>4770</u>			
<u>2 Lansing</u>		<u>4143</u>			
<u>3 Kansas City "A"</u>		<u>4602</u>			

WATER SANDS

NAME	FROM	TO	WATER LEVEL	NAME	FROM	TO	WATER LEVEL
<u>1 Not Known</u>							
<u>2</u>							

CASING RECORD (OVERALL MEASUREMENT)

LINER-SCREEN RECORD

CSG. SIZE	WEIGHT	DESCRIPTION		QUANTITY FEET	SIZE	QUANTITY FEET	SET AT		MAKE AND TYPE
		THREADS	MAKE - GRADE				TOP	BOTTOM	
<u>8-5/8</u>	<u>24</u>	<u>8 T</u>	<u>J-55</u>	<u>734</u>					
<u>5-1/2</u>	<u>14</u>	<u>8 T</u>	<u>J-55</u>	<u>5026</u>					

PACKER RECORD

SIZE	LENGTH	SET AT	MAKE AND TYPE

CEMENTING RECORD

MUDDING RECORD

SIZE	WHERE SET FEET	CEMENT			METHOD	FINAL PRESS	(CABLE TOOLS)	
		SACKS	BRAND	TYPE			METHOD	RESULTS
<u>8-5/8</u>	<u>738</u>	<u>650</u>	<u>Pozmix</u>	<u>Bulk</u>	<u>Halliburton</u>			
<u>5-1/2</u>	<u>4999</u>	<u>210</u>	<u>Pozmix</u>	<u>Bulk</u>	<u>Halliburton</u>			

RECEIVED
STATE CORPORATION COMMISSION

DEC 21 1962

WHAT METHOD WAS USED TO PROTECT SANDS WHEN OUTER STRINGS WERE PULLED? _____ CONSERVATION DIVISION
Wichita, Kansas
WERE BOTTOM HOLE PLUGS USED? _____

IF SO, STATE KIND, DEPTH SET, AND RESULTS OBTAINED _____

ROTARY TOOLS WERE USED FROM 0 FEET TO 5000 FEET, AND FROM _____ FEET TO _____ FEET

CABLE TOOLS WERE USED FROM to test FEET TO _____ FEET, AND FROM _____ FEET TO _____ FEET

24-HOUR PRODUCTION OR POTENTIAL TEST Dry hole

_____ WATER _____ BBLs.

IF GAS WELL, CUBIC FEET PER 24 HOURS _____ SHUT-IN PRESSURE _____ LBS. PER SQUARE IN.

I, THE UNDERSIGNED, BEING FIRST DULY SWORN UPON OATH, STATE THAT THIS WELL RECORD IS TRUE AND CORRECT ACCORDING TO THE RECORDS OF THIS OFFICE AND TO THE BEST OF MY KNOWLEDGE AND BELIEF.

Original Signed by
D. M. LILES Area Supt.

SUBSCRIBED AND SWORN TO BEFORE ME THIS 10 DAY OF December 19 62

MY COMMISSION EXPIRES Dec. 3, 1964 R. W. Banks NOTARY PUBLIC

FORMATION RECORD

DESCRIBE EACH FORMATION DRILLED. INDICATE THICKNESS, CONTENT AND WHETHER DRY, OR OIL, GAS, OR WATER BEARING.

FORMATION	TOP	BOTTOM	FORMATION	TOP	BOTTOM
Surface clay, sand	0	500			
Sand, Redbed	500	750			
Redbed, Shale	750	1263			
Sand, Shale	1263	1811			
Shale	1811	2186			
Lime, Shale	2186	2880			
Lime	2880	3839			
Lime, Shale	3839	4100			
Lime	4100	5000			
Total Depth		5000			
Completed as dry hole					