

To: 1 060745
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 185-22,320-0000
NE NE NW, SEC. 25, T 22 S, R 12 W/EX
4950 feet from S section line
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6039
Operator: L. D. Drilling, Inc.
Name
Address R. R. 1, Box 183B
Great Bend, KS 67530

Lease Name Heyen "B" Well # 1
County Stafford
Well Total Depth 3662 Arbuckle 5' 119.02 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 261

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor L. D. Drilling, Inc. License Number 6039
Address R. R. 1, Box 183B, Great Bend, KS 67530

Company to plug at: Hour: 8:00 pm Day: 16 Month: December Year: 19 85

Plugging proposal received from Don Pope

(company name) L. D. Drilling (phone) 316-793-3051
Elevation 1856'

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 600-30'
1st plug in the Arbuckle with 40 sx cement if 50' or more

2nd plug at the base of the Anhydrite with 50 sx cement

3rd plug 50' below the base of the surface pipe with 50 sx cement
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement. Plug water well from bottom to top with cement
Plugging Proposal Received by Paul A. Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 10:45 pm Day: 16 Month: December Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 3615' with 50 sx cement, 2nd plug at 600' with 50 sx
cement, 3rd plug at 270' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls - plug
at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with 15 sx
cement, and plugged water well with 5 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton
(if additional description is necessary, use BACK of this form.)

INVOICED
I (and did not) observe this plugging.

Signed Paul A. Luthi
(TECHNICIAN)

DATE DEC 20 1985
INV. NO. 1167

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date ... December 3, 1985

API Number 15- 185-22,320-0000

OPERATOR: License # 6039
Name L. D. Drilling, Inc
Address R.R. 1, Box 183, B
City/State/Zip Great Bend, KS 67530
Contact Person L. D. Davis
Phone (316) 793-3051

NE NE NW Sec. 25 Twp. 22 S, Rg. 12
4950 Ft. from South Line of Section
2970 Ft. from East Line of Section
(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 6039
Name Company tools
City/State

Nearest lease or unit boundary line 330 feet
County Stafford
Lease Name Heyen "B" Well # 1
Ground surface elevation estimate 1856 feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Surface pipe by Alternate: 1 X 2
Depth to bottom of fresh water 160
Depth to bottom of usable water 220
Surface pipe planned to be set 250'
Projected Total Depth 367.5 feet
Formation Arbuckle

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl Wildcat Cable

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 11-27-85 Signature of Operator or Agent L. D. Davis Title President/Operator

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required feet per Alt. 1 2
This Authorization Expires 12-2-85 Approved By RCH 12-2-85

Form C-1 6/85

PLUGGING PROPOSAL ABOVE IS D & A 35' set 250'

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 3645 arbuckle feet depth with 40
2nd plug @ 600 cement feet depth with 50
3rd plug @ 400 ft. return feet depth with 40
4th plug @ 40 feet depth with 10
5th plug @ feet depth with
(2) Rathole with 15 sxs (b) Mousehole with sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. Important: Call district office after well is either plugged or production casing is cemented in.

(Call 7 a.m. to 5 p.m. workdays)

District office use only:
API # 15-185-22,320
Surface casing of feet set with sxs at hours 19
Alternate 1 or 2 surface pipe was used.
Alternate 2 cementing was completed @ ft. depth with sxs of 19
Hole plugged 19, agent

RECEIVED STATE CORPORATION COMMISSION

RECEIVED KCC-KDHE DEC 3 1985 JOINT DISTRICT HAYES

DEC 2 1985

Wichita, Kansas