

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-185-21,462-0000

SE/4 Sec. 33, T 22 S, R 14 W/E

SESW SE feet from N/S section line

TECHNICIAN'S PLUGGING REPORT

\_\_\_\_\_ feet from W/E section line

Operator License # 6393

Lease Name Miller Well # 13-2

Operator: Broogher oil Inc  
Name & P.O. Drawer 1367  
Address Great Bend KS 67530

County Stafford

Well Total Depth 4015 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 261' 225'

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Rock Hold Eng Inc License Number 5111 tag 93

Address Box 698 Great Bend KS

Company to plug at: Hour: 1:00pm Day: 25 Month: Jan Year: 19 83

VERBAL PLUGGING ORDERS GIVEN TO Pellog

(company name) Rock hold Eng. Inc (phone) \_\_\_\_\_

were: 4 1/2 set of 4010' with 175 sy top perf 3658-63  
Sand back to 3600, 4 sy cement with boiler, Recovered  
3600' of 4 1/2. Squeezed well with 3 sy Hulls 70  
sy cement 25 sy gel 1 sy Hull 120 sy cement 5050  
reg 49 gel 79 cc

Signed J. A. May (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 5:00pm Day: 25 Month: Jan Year: 19 83

ACTUAL PLUGGING REPORT Squeezed well with 3 sy Hull 70  
sy cement 25 sy gel 1 sy Hull, Released plug  
120 sy cement may press 500# Shotfrn 200'

Remarks: Cemented by Adhesive

I hereby certify that the above plugging instructions were given as herein stated and that I (did / did not) observe this plugging.

INVOICED  
DATE 2-7-83  
INV. NO. 2336-4

RECEIVED  
STATE CORPORATION COMMISSION  
JAN 31 1983  
CONSERVATION DIVISION  
Wichita, Kansas

Signed J. A. May (TECHNICIAN)