

1 120480

10-9

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-145-20,554-0000

E/2 E/2 SE, SEC. 31, T. 22 S, R. 15 W/EX

1320 feet from S section line

330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5298

Lease Name Bowman Well # B-1

Operator: Gould Oil, Inc.

County Pawnee 123.50

Name & Address 110 N. Market, #411

Well Total Depth 3800 feet

Wichita, KS 67202

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 346

Abandoned Oil Well _____ Gas Well Input Well _____ SWD Well _____ O&A _____

Other well as hereinafter indicated _____

Plugging Contractor Pratt Well Service License Number 5893

Address N. Highway 61, Pratt, KS 67124

Company to plug at: Hour: 9:30 a.m. Day: 9 Month: 10 Year: 19 90

Plugging proposal received from Ken Gates

(company name) Pratt Well Service (phone) 316-672-2531

were: 4 1/2" at 3029' w/175 sx cement, PRTD 3029', Perfs at 2864-70'

1st plug sand 4 1/2" casing back to 2765' with 4 sx cement on top of sand through bailer,

2nd plug pump 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls,

release 8 5/8" wiper plug and pump 150 sx cement.

Plugging Proposal Received by Dan Goodrow
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 11 a.m. Day: 9 Month: 10 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug sanded 4 1/2" casing back to 2765' and dumped 4 sx cement on top of sand through bailer,

2nd plug pumped into 8 5/8" surface casing with 300 lbs. hulls, 10 sx gel, 50 sx cement,

10 sx gel, 150 lbs. hulls, and 150 sx cement.

Pumping pressure 0-450 psi and shut in 300 psi.

Remarks: Used 60/40 Pozmix 6% gel by HOWCO. Recovered 2421' of 4 1/2" casing.

(If additional description of conditions necessary, use BACK of this form.)

INVOICED

STATE CORPORATION COMMISSION

DATE 10-22-90

OCT 17 1990

Signed Duane Rankin
(TECHNICIAN)

INV. NO. 29690

CONSERVATION DIVISION
Wichita, Kansas