## 16.083.20372.00.00

Form CP-3 Rev. 6-4-68

## STATE CORPORATION COMMISSION

## CONSERVATION DIVISION AGENT'S REPORT

RECEIVED STATE CORPORATION COMMISSION

AUG 1 3 1974

CONSERVATION DIVISION Wichita, Kansas

J, Lewis Brock Administrator P. O. Box 17027 Wichita, Kansas 67217

	Complete Address			····				<del></del> -
	Lease Name	Everto	n .			ll No		<del></del> _
•	Location	C NW S	E 		_Sec31	_Twp21	Rge. 24 (E)	(W)
	County	Hodgem	an .			_Total Dep	th 4715	<del></del>
	Abandoned Oil We	11X	Gas Well	Input	t Well	SWD W	ellI	% A
	Other well as he	reafter i	ndicated					
	Plugging Contrac	tor R	ockhold En	gineering			_	
		98, Great Bend, Kansas						
			- Mαρρ. Γ		_			
8 <b>5</b> .	Operation Comple  The above well w	as plugge	ed as follows	s:		<del></del> -	8 . Year	*,
		rulated	ed as follows w/ cement	s:	1/2" t	:0 l <sub>4</sub> 710'	cemented.	*,
Top	The above well w	ras plugge rulated 4646'	ed as follows  w/ cement  Plug	· 5	1/2" t	0 4710' Plug At	cemented.	*,
Top Mud	The above well w/8" to 675' ci	ras plugge rulated 4646†	ed as follows  w/ cement  Plug  Spott	s: 5 bottom w/	1/2" t Bridge ks ceme	o 4710' Plug At	cemented. : 1,622' to <b>3</b> 50'	*,
Top Mud Mud	The above well w/8" to 675' ci perforations 4622' to 500'	ras plugge rulated 4646†	ed as follows  w/ cement  Plug  Spott  Plug	s:  bottom w/ ed 50 sacl	1/2" t Bridge ks ceme s cemer	o 4710' Plug At nt 500'	cemented. : 4622' to \$50'	*,
Top Mud Mud	The above well w/8" to 675' ci perforations 4622' to 500' 350' to 150'	ras plugge rulated 4646†	ed as follows  w/ cement  Plug  Spott  Plug	bottom w/ed 50 sack	1/2" t Bridge ks ceme s cemer	o 4710' Plug At nt 500'	cemented. : 4622' to \$50'	*,
Top Mud Mud	The above well w/8" to 675' ci perforations 4622' to 500' 350' to 150'	ras plugge rulated 4646†	ed as follows  w/ cement  Plug  Spott  Plug	bottom w/ed 50 sack	1/2" t Bridge ks ceme s cemer	o 4710' Plug At nt 500'	cemented. : 4622' to \$50'	*,
Top Mud Mud	The above well w/8" to 675' ci perforations 4622' to 500' 350' to 150'	ras plugge rulated 4646†	ed as follows  w/ cement  Plug  Spott  Plug	bottom w/ed 50 sack	1/2" t Bridge ks ceme s cemer	o 4710' Plug At nt 500'	cemented. : 4622' to \$50'	*,
Top Mud Mud	The above well w/8" to 675' ci perforations 4622' to 500' 350' to 150'	rulated	ed as follows  w/ cement  Plug  Spott  Plug  Fulle	bottom w/ ed 50 sack & 50 sack d 3830' of	1/2" t Bridge ks cemer s cemer	Plug At nt 500' at 150' t	cemented.  L 4622'  to 350'  to 0'.	*,