) To: ,	1040804 (1-7)	' API NUMBER 15- 14	5-20,313-0000
STATE CORPORATION COMMISSION  CONSERVATION DIVISION - PLUGGING SECTION  200 (COLORADO DERBY BUILDING		W/2 W/2 NE, SEC. 13 , T 22 S, R 18 W/K	
	KANSAS 67202	3960	leet from S section line
TECHNICIA	N'S PLUGGING REPORT	2310	feet from E section line
	License J 5086	Lesse Name Strobel	Well # 2
Operator: Name& Address	Pintail Petroleum Ltd.	County Pawnee	
	225 N. Market, Ste. 300	Well Total Depth_	Well Total Depth 4208 36.76 feet
	Wichita, KS 67202		zetest
		Surface Casing: Si	lze 8 5/8 feet 244
Abandoned	Oll Well X Gas Well	_ input Well S	SWD Well D&A
	i as hereinafter indicated		
	P.O. Box 347, Chase, KS 67524		
Address	P.O. Box 347, Chase, KS 67524	11	11 00
Company 1	to plug at: Hour: 3:30 p.m. Day:	11 Month:	Year:1993
Plugging	proposal received from Mike Kelso		<del></del>
(company	name) Kelso Casing Pulling, Inc.		(phone)_316-938-2943
vere:	3½" at 4207' w/100 sx cement, PBTD 4	147', Perfs at 4099-411	.21
lst plug	sand back to 4050 and dump 5 sx cem	ent on top of sand throu	ıgh bailer,
2nd plug	perforate at 1100' and pump 175 sx c	ement.	
-	5/8" annulus had been squeezed in the		
_ <u> </u>	annulus nad been syneezed in the	past.	· · · · · · · · · · · · · · · · · · ·
	Plusales Pass		Duane Rankin
<del></del>	Plugging Prop	osal Received by T	(TECHNICIAN)
Plugging	Operations attended by Agent7: A	NiPart	None X
Operation	ns Completed: Hour:4:30 p.m. Day:	11 Month:	11 Year: 19 93.
	LUGGING REPORT 1st plug sanded back		
		To jose and damped 5 b.	
bridge tr	nrough bailer,	<del></del>	
	perforated 55" casing at 1100'. Pum	<u> </u>	n 180 sx cement.
Maximum p	pressure 1000 psi and shut in 750 psi	·	RECEIVED
5½" X 8 5	5/8" annulus had been squeezed in the	past. Pressured up on	annulustate c 1000 tic OKommission
		•	NOV 1 8 1993
Remarks:	Used 60/40 Pozmix 6% gel by Allied	No casing recovery	90
I AL V	Out and tional description is		of this formbile, Kensee
xxxx)	Odia god 35 beerve this plugging.	01	
		Signed Stad	hem I the Su
₩V. MO	39288.		TECHNIOTANY
	<u> </u>		FORM CP-2/