

1 120509

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-185-22,743-0000  
NE NW SW, SEC. 34, T 22 S, R 12 W/E  
2310 feet from S section line  
4290 feet from E section line  
Lease Name Esther Allen Well # 1-34  
County Stafford 121.87  
Well Total Depth 3750 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 265

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5107  
Operator: H-30 Drilling, Inc.  
Name & Address 251 N. Water, Suite 10  
Wichita, KS 67202

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SMD Well \_\_\_\_\_ D&A x  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor H-30 Drilling, Inc. License Number 5107  
Address 251 N. Water, Suite 10, Wichita, KS 67202

Company to plug at: Hour: 4:30 p.m. Day: 18 Month: 12 Year: 19 90  
Plugging proposal received from Alan Leslie  
(company name) H-30 Drilling, Inc. (phone) 316-263-2043

work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 680-720'  
1st plug at 730' with 50 sx cement,  
2nd plug at 295' with 50 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Case Morris  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_  
Operations Completed: Hour: 6 p.m. Day: 18 Month: 12 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug at 730' with 50 sx cement,  
2nd plug at 295' with 50 sx cement,  
3rd plug at 40' with 10 sx cement,  
4th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
DEC 21 1990  
12-21-90  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

I (did ~~not~~) observe this plugging.

Signed Case Morris  
(TECHNICIAN)

DATE JAN 09 1991  
INV. NO 30417  
12-18

EFFECTIVE DATE: 12-15-90

15-185-22743-0000  
Correction

FORM MUST BE TYPED  
FORM C-1 4/90

State of Kansas  
NOTICE OF INTENTION TO DRILL 185-22743

FORM MUST BE SIGNED  
ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date October 21, 1990  
month day year

NE. NW. SW. Sec. 34. Twp. 22. S. Rg. 12.  East  
 West

OPERATOR: License # 5107  
Name: H-30 Drilling, Inc.  
Address: 251 N. Water, Suite 10  
City/State/Zip: Wichita, KS 67202  
Contact Person: Jeffrey A. Burk  
Phone: (316) 263-2043

2310 feet from South line of Section  
4290 feet from East line of Section  
(Note: Locate well on Section Plat on Reverse Side)

CONTRACTOR: License #: 5107  
Name: H-30 Drilling, Inc.

County: Stafford  
Lease Name: Ether Allen Well #: 1-34  
Field Name: Wildcat

Well Drilled For: Well Class: Type Equipment:  
 Oil ... Inj ... Infield  Mud Rotary  
 Gas ... Storage ... Pool Ext. ... Air Rotary  
... CWMO ... Disposal  Wildcat ... Cable  
... Seismic; ... # of Holes

Is this a Prorated Field? ... yes  no  
Target Formation(s): Lansing, Viola, Arbuckle  
Nearest lease or unit boundary: 330'  
Ground Surface Elevation: 1832' East feet MSL  
Domestic well within 330 feet: ... yes  no  
Municipal well within one mile: ... yes  no  
Depth to bottom of fresh water: 160'  
Depth to bottom of usable water: 300'  
Surface Pipe by Alternate:  1 ... 2  
Length of Surface Pipe Planned to be set: 250'  
Length of Conductor pipe required: N/A  
Projected Total Depth: 3,850'  
Formation at Total Depth: Arbuckle  
Water Source for Drilling Operations:

If CWMO: old well information as follows:  
Operator:  
Well Name:

RECEIVED  
STATE CORPORATION COMMISSION

DEC 21 1990

Pusher John Leslie  
 SPUD DATE 12-10-90 INIT. CA  
 LENGTH SURFACE PLANNED \_\_\_\_\_  
 RESERVE PIT STATUS REMOVE FLUID \_\_\_\_\_ LINED \_\_\_\_\_  
 after salt sect. \_\_\_\_\_ bbls. \_\_\_\_\_ when done \_\_\_\_\_ bbls.  
 RATHOLED AHEAD? Y \_\_\_\_\_ N \_\_\_\_\_ SIZE HOLE \_\_\_\_\_  
 SURFACE PIPE 8 7/8 @ 265 CONDUCTOR \_\_\_\_\_  
 ANHYDRITE T- 680 B- 720 ELEVATION \_\_\_\_\_  
 TD 3750 FORMATION \_\_\_\_\_  
 RAN PIPE @ \_\_\_\_\_ DV TOOL \_\_\_\_\_ ALT II DONE \_\_\_\_\_  
 \_\_\_\_\_ SX \_\_\_\_\_ SX Y \_\_\_\_\_ N \_\_\_\_\_  
 \_\_\_\_\_ Arbuckle Plug @ \_\_\_\_\_ Ft. W/ \_\_\_\_\_ SX  
 \_\_\_\_\_ Hug./Council @ \_\_\_\_\_ Ft. W/ \_\_\_\_\_ SX  
 \_\_\_\_\_ Anhydrite Base @ 730 Ft. W/ 50 SX  
 \_\_\_\_\_ 1/2 Base Anhyd. @ \_\_\_\_\_ Ft. W/ \_\_\_\_\_ SX  
 \_\_\_\_\_ 1/2, 1/2 Plug @ \_\_\_\_\_ Ft. W/ \_\_\_\_\_ SX  
 \_\_\_\_\_ Bottom Surface @ 295 Ft. W/ 50 SX  
 \_\_\_\_\_ 40' Plug @ 40 Ft. W/ 10 SX  
 RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ \_\_\_\_\_ SX  
 WATER WELL \_\_\_\_\_ SX (Irr. Well \_\_\_\_\_ Pond \_\_\_\_\_)  
 \_\_\_\_\_ Hauling \_\_\_\_\_  
 TECHNICIAN CA DATE 12-8-90  
 TYPE OF CEMENT 60/40 675  
 STARTING TIME 4:30 (AM/PM) DATE 12-18-90  
 COMPLETION TIME 6:00 (AM/PM) DATE 11  
 CEMENT COMPANY Applied  
Rambin Saw