

1 020382

To:

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 5886Operator: Chief Drilling, Inc.Name & Address 224 E. Douglas, Suite 530Wichita, KS 67202API NUMBER 19-055-21,003-0000C NW NW, SEC. 11, T 22, S, R 30 W/E4620 feet from S section line4620 feet from E section lineLease Name Rumford Well # 1-11County Finney 154.70Well Total Depth 4760 feetConductor Pipe: Size feetSurface Casing: Size 8 5/8 feet 270Abandoned Oil Well Gas Well Input Well SWD Well D&A XOther well as hereinafter indicated Plugging Contractor Chief Drilling, Inc. License Number 5886Address 224 E. Douglas, Suite 530, Wichita, KS 67202Company to plug at: Hour: 5:45 a.m. Day: 6 Month: 6 Year: 19 91Plugging proposal received from Marion Burris(company name) Chief Drilling, Inc. (phone) 316-262-3791

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2040' with 50 sx cement, 2nd plug at 1100' with 50 sx cement,

3rd plug at 550' with 40 sx cement, 4th plug at 300' with 50 sx cement,

5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,

7th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Glenn Barlow
(TECHNICIAN)Plugging Operations attended by Agent?: All Part None XOperations Completed: Hour: 8 a.m. Day: 6 Month: 6 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug at 2040' with 50 sx cement,

2nd plug at 1100' with 50 sx cement,

3rd plug at 550' with 40 sx cement,

4th plug at 300' with 50 sx cement,

5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,

7th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix-6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED

(XXX) did not observe this plugging.

DATE 6-20-91INV. NO. 322006-6Signed Glenn R. Barlow
(TECHNICIAN)

EFFECTIVE DATE: 5-22-91

State of Kansas

15-055-21,003-0000

FORM MUST BE SIGNED

ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 5-21-91
month. day year

C NW NW Sec 11 Twp 22S S, Rg 30W East West

OPERATOR: License # 5886
Name: Chief Drilling, Inc.
Address: 224 E. Douglas, #530
City/State/Zip: Wichita, Kansas, 67202
Contact Person: Douglas W. Thimesch
Phone: 316 262-3791

4620 feet from South line of Section
4620 feet from East line of Section
(Note: Locate well on Section Plat on Reverse Side)

CONTRACTOR: License #: 5886
Name: Chief Drilling, Inc.

County: Finney
Lease Name: Rumford Well #: #1-11
Field Name: UNNAMED

Is this a Prorated Field? yes X no
Target formation(s): Morrow, Mississippi

Nearest lease or unit boundary: 660
Ground Surface Elevation: NA feet MSL

Domestic well within 330 feet: yes X no

Municipal well within one mile: yes X no

Depth to bottom of fresh water: 130

Depth to bottom of usable water: 1200

Surface Pipe by Alternate: 1 X 2

Length of Surface Pipe Planned to be set: 250

Length of Conductor pipe required: -0-

Projected Total Depth: 4800

Formation at Total Depth: Mississippi

Water Source for Drilling Operations:

well farm pond X other

DWR Permit #:

Will Cores Be Taken?: yes X no

If yes, proposed zone: STATE CORPORATION COMMISSION

Well Drilled For: Well Class: Type Equipment:
X Oil Inj Infield X Mud Rotary
Gas Storage Pool Ext. H.C. RATED
OWO Disposal X Wildcat
Seismic; # of Holes

If OWO: old well information as follows:

Operator: CONSERVATION DIVISION
Well Name: Wichita, Kansas
Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no

If yes, total depth location:

Exp. 11/17/91

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following minimum requirements will be met:

CONSERVATION DIVISION
Wichita, Kansas

Pusher: MASON BORDEN
SPUD DATE: May 28, 1991 INIT. CB
LENGTH SURFACE PLANNED: 250' of 8 5/8"
RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 8 5/8" @ 27' CONDUCTOR
ANHYDRITE T- B- ELEVATION
TD 4760' FORMATION
RAN PIPE @ SX DV TOOL ALT II DONE
Arbuckle Plug @ Ft. W/ SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ 2040 Ft. W/ 5' SX
1/2 Base Anyh. @ 1100 Ft. W/ 50' SX
1/2, 1/2 Plug @ 550 Ft. W/ 40' SX
Bottom Surface @ 300 Ft. W/ 50' SX
40' Plug @ 40 Ft. W/ 10' SX
RAT HOLE CIRC/W 15' SX MOUSE HOLE W/ 10' SX
WATER WELL SX (Irr. Well Pond Hauling
TECHNICIAN G.B. DATE
TYPE OF CEMENT 60
STARTING TIME 5:45 (AM/PM) DATE 6-6-91
COMPLETION TIME 8:00 (AM/PM) DATE 6-6-91
CEMENT COMPANY Allwell