2-28	15-185-12260-10-01	240/
	- 1 //- 00 770	~را

To:		API NUMBER 15-	Docket #D-23,77	0	
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		NE SW NW, SEC.		s, r <u>14</u> w/k	
TECHNICIA	N'S PLUGGING REPORT	4290	feet from E	section line	
Operator	License / 30180	Hatha	way-Ukens	2 SWD	
Operator:	U-H 0il Company		ford		
Nameš Address	P.O. Box 42	Woll Total Depth 4151 feet			
	Hudson, KS 67545	Conductor Pipe:	S1ze	feet	
		Surface Casing:	Size <u>8 5/8</u> fe	e† <u>410</u>	
Abandoned	Oll Well Gas Well	Input Well	SWD WellX	D&A	
Other wei	l as hereinafter indicated			·	
Plugging	Contractor Klima Well Service		License Number	7023	
Address	P.O. Box 386, Claflin, KS 67525	<del></del>			
Company †	o plug at: Hour: 8 a.m. Day:	23Month:	Yea	r:19 <sup>90</sup>	
	proposal received from Monte Cha				
(company	name) U-H Oil Company			16-458-4651	
were: 5½" casing set at 3910' cemented w/100 sx cement Open hole					
1st plug run tubing to 1300' and spot 50 sx cement plug,					
2nd plug perforate 5½" casing at 850' and circulate cement.					
	······································				
	Plugging Prop	osal Received by			
	,		(TECHNIC		
	Operations attended by Agent?: A				
	is Completed: Hour: 1 p.m. Day:				
	UGGING REPORT 2/23/90 Ran bubing lug in five hours, no plug, pumpe				
	pumped 50 sx 60/40 6%, set four he 6%. 2/26/90 Ran tubing to 1300				
	s, fiber, and celo flakes, follow plug. 2/27/90 Ran tubing to 13				
	gel, hulls, fiber, and celo seal for Ran tubing to 1300', no plug. Pum				
tubing to	o 1240', tubing stacked out. Performed hole with 240 sx 60/40 6% plus	orated the 5½"casin	g 849-850' and o	circulated	
tubing an	nd topped $5\frac{1}{2}$ casing with 10 sx Th	rifty Mix cement.			
	ed MTT on 2/1/90. Operator found Cemented by B.J. Titan. No casin				
NVOI	ON Enth poddifficional description is	necessary, use BAC	CK of this form.	· (X	
TĪ (dlā/	MXXXXXX) observe this plugging.	Λ	01'	32	

FORM CP-2/3 Rev.01-84