		3-3-88	W 185, 2N	Din ecco
, ° 1051	1013			
o: STATE CORPORATION CO		AP1 NUMBER 15-D	rill Completion	
CONSERVATION DIVISIO	N - PLUGGING SECTION UILDING	NW SE NE , SEC.	18. T 23 S	, R <u>12</u> ₩/K
WICHITA, KANSAS 67202		3630	feet from S s	section line
ECHNICIAN'S PLUGGIN	G REPORT	990	feet from Es	section line
perator Licensé 🚛	5992	Lease NameDale	eWell#_	1
Operator: Patton Oil Company		County Stafford	đ	126.75
lameå Address <u>672 West 4</u>	th Street	Well Total Depth	3900	feet
Hoisington	n, KS 67544	Conductor Pipe:	Slzefe	3e†
		Surface Casing:	Size <u>8 5/8</u> feet	239
(bandoned Oll Well	X Gas Well	Input Well	_ SWD Well	D&A
)ther well as herein	after Indicated			
'lugging Contractor_	Kelso Casing Pulling		License Number_	6050
ddress P.O. Box 347	7, Chase, KS 67524			
Company to plug at:	Hour: 10 a.m. Day:	3 Month:	3 Year:	19 88
	ceived from Clay Dunt:			
•	so Casing Pulling		(phone) 316	6-938-2457
	PBTD 3862 Perfs at 3	•		
	o 3550' and dump 5 sx			<del></del>
	nulls, 10 sx gel, 50 sx	<del></del>		
viper plug and pump	<u> </u>		<del></del>	<del></del>
ipor prog and pump	100 on contents.			<del></del>
	Plugging Prop	osal Received by	Richard Lacev	
			(TECHNICIA	(N)
lugging Operations	attended by Agent1: Al	IIX Part_	None	
perations Completed	: Hour: 11:15 a.mQay:_	3 Month:	3 Year:	:19_88
CTUAL PLUGGING REPO	RT 1st plug sanded bac	ck to 3550° and dump	ped 5 sx cement o	on top of
sand through bailer,				<del></del>
2nd plug pumped down	n 8 5/8" with 4 sx hulls	s, 10 sx gel, 50 sx	cement, 10 sx ge	el, 1 sx
nulls, released 8 5/	8" wiper plug and pumpe	ed 100 sx cement.		
·				AFE CORPORATION CURIS,
Maximum pressure 500	) psi and shut in 300 ps	si.		N:AR - 7 1988
Remarks: Used 60/40	Pozmix 6% gel by Allie	ed. Recovered 2908		CONSERVATION DIVISION
(If add	itional description is			Vilahita, Kanses
	serve this plugging.	2-11	aust	$\varphi$
TE	á.	Signed Ruchard	W. Jacky (TECHNICHAN)	

FORM CP-2/3 Rev.01-84